

Job Q104-179RT	Truss C01	Truss Type Piggyback	Qty 25	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	-------------------------	-----------	----------	-----------------------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:35 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-dszWbJJITtq3iZH26PnPDPiQDEyRtmrrEzCSiz477E

4-0-0
4-0-0

8-0-0
4-0-0

4x4 =

Scale = 1:24.9




Plate Offsets (X,Y)-- [2:0-2-6,0-1-0], [4:0-2-6,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.26	Vert(LL) 0.01	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.10	Vert(CT) 0.01		
TCDL 10.0	Rep Stress Incr YES	WB 0.04	Horz(CT) 0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 24 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=244/6-10-10 (min. 0-1-8), 4=244/6-10-10 (min. 0-1-8), 6=267/6-10-10 (min. 0-1-8)
Max Horz 2=66(LC 12)
Max Uplift 2=25(LC 14), 4=25(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (11)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-2-10 to 3-2-10, Interior(1) 3-2-10 to 4-0-0, Exterior(2) 4-0-0 to 7-0-0, Interior(1) 7-0-0 to 7-9-6 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 25 lb uplift at joint 2 and 25 lb uplift at joint 4.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 11) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss C01G	Truss Type GABLE	Qty 2	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:04:05 2021 Page 1

ID:k67_5nKOKmb2GQsoap?Ao4zlytl-Ej1D4b8r8onY216rc5y1vKYhRyaiYwLZl8i?z474u

4-0-0 8-0-0 4-0-0

4x4 =

Scale = 1:26.1




Plate Offsets (X,Y)-- [2:0-2-6,0-1-0], [4:0-2-6,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.26	Vert(LL) 0.01	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.04	Vert(CT) 0.01		
TCDL 10.0	Rep Stress Incr YES	WB 0.00	Horz(CT) 0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 27 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 6-10-10.
(lb) - Max Horz 2=66(LC 12)
Max Uplift All uplift 100 lb or less at joint(s) 2, 4
Max Grav All reactions 250 lb or less at joint(s) 7, 8, 6 except 2=319(LC 1), 4=319(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-11=-276/38, 4-14=-276/38

NOTES- (13)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-2-10 to 3-2-10, Interior(1) 3-2-10 to 4-0-0, Exterior(2) 4-0-0 to 7-0-0, Interior(1) 7-0-0 to 7-9-6 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 2-0-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 13) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss C02	Truss Type Piggyback	Qty 31	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:37 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-ZE5G0?L??K7Y1?jAXRFIqn6O0wvnm8JYSIXaz477C

2-0-0 4-0-0
2-0-0 2-0-0

Scale = 1:12.2




Plate Offsets (X,Y)-- [2:0-2-6,0-1-0], [4:0-2-6,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.04	Vert(LL) 0.00 in (loc) 4 l/defl n/r 120	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.02	Vert(CT) 0.00 4 n/r 120		
TCDL 10.0	Rep Stress Incr YES	WB 0.01	Horz(CT) 0.00 4 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 11 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=120/2-10-10 (min. 0-1-8), 4=120/2-10-10 (min. 0-1-8), 6=108/2-10-10 (min. 0-1-8)
Max Horz 2=31(LC 12)
Max Uplift 2=16(LC 14), 4=16(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (11)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 16 lb uplift at joint 2 and 16 lb uplift at joint 4.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 11) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss C02G	Truss Type Piggyback	Qty 3	Ply 1	BANDY RESIDENCE
-------------------	---------------	-------------------------	----------	----------	-----------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:12:39 2021 Page 1

ID:k67_5nOKmB2GQsoap?Ao4zlytl-Ab5XyMMF5jXcjKuyZJV8QCEKtb0AfaXXpJIDz46ys

2-0-0 4-0-0
2-0-0 2-0-0

Scale = 1:12.2




Plate Offsets (X,Y)-- [2:0-2-6,0-1-0], [4:0-2-6,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.04	Vert(LL) 0.00 in (loc) 4 l/defl n/r 120	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.02	Vert(CT) 0.00 4 n/r 120		
TCDL 10.0	Rep Stress Incr YES	WB 0.01	Horz(CT) 0.00 4 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 11 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=120/2-10-10 (min. 0-1-8), 4=120/2-10-10 (min. 0-1-8), 6=108/2-10-10 (min. 0-1-8)

Max Horz 2=31(LC 12)

Max Uplift 2=16(LC 14), 4=16(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (11)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 11) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE-BUDGET ONLY
Q104-179RT	C03	Piggyback	19	1	
Job Reference (optional)					

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:38 2021 Page 1
24-14141-1P/KR14141-1P-21-15-11-14KHE2G-B20142P-24-17P

ID:k67_5nOKmB2GQsoap?Ao4zlytl-1RffDKMdmdFP

2-0-0	4-0-0
2-0-0	2-0-0

Scale = 1:10.5




Plate Offsets (X,Y)-- [2:0-2-1,0-1-0], [4:0-2-1,0-1-0]

LUMBER-

EMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=116/2-8-14 (min. 0-1-8), 4=116/2-8-14 (min. 0-1-8), 6=109/2-8-14 (min. 0-1-8)
Max Horz 2=24(LC 12)
Max Vert 2=47(LC 14), 4=47(LC 14)

FORCES (lb) - Max. Comp./Max. Tens. - All forces 350 (lb) or less except when shown

NOTES- (11)

NOTES- (11)


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 2 and 17 lb uplift at joint 4.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TP1 1.
- 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 11) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss CJ01	Truss Type Diagonal Hip Girder	Qty 2	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:23 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-D5tfgjvsASw0p4EVsBG2AXhugZctgZvuuibk8wz476U

-1-2-14 3-6-1 7-0-2
1-2-14 3-6-1 3-6-1

Scale = 1:34.0



3-6-1 7-0-2
3-6-1 3-6-1

Plate Offsets (X,Y)-- [2:0-1-12,0-1-8], [3:0-1-12,0-1-8], [7:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.36	Vert(LL) 0.01 in (loc) 8-9 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.12	Vert(CT) -0.01 8-9 >999		
TCDL 10.0	Rep Stress Incr NO	WB 0.09	Horz(CT) -0.00 7 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 36 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=408/0-7-15 (min. 0-1-8), 7=340/Mechanical
Max Horz 9=137(LC 9)
Max Uplift 9=-133(LC 10), 7=-92(LC 7)
Max Grav 9=421(LC 38), 7=349(LC 37)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-9=-386/114, 2-10=-350/94, 3-10=-251/87
WEBS 2-8=-70/278, 3-7=-296/120

NOTES- (11)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7 except (jt=lb) 9=133.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-2=-82, 2-4=-82, 4-5=-82, 6-9=-20

Continued on page 2

Job Q104-179RT	Truss CJ01	Truss Type Diagonal Hip Girder	Qty 2	Ply 1	BANDY RESIDENCE-BUDGET ONLY Job Reference (optional)
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:23 2021 Page 2 ID:k67_5nOKmB2GQsoap?Ao4zlytl-D5tfgjvsASw0p4EVsBG2AXhugZctgZvuuibk8wz476U

LOAD CASE(S) Standard

Concentrated Loads (lb)

Vert: 10=63(F=31, B=31) 13=-1(F=-1, B=-1)

Job Q104-179RT	Truss CJ02	Truss Type Diagonal Hip Girder	Qty 1	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	---------------	-----------------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:21:07 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-uvJX7043fv5kZ2NQbJ0qdjLB_ru1W5XFAfwix6z45yg
-1-3-9
1-3-9
4-3-1
4-3-1
4-6-9
0-3-8




Plate Offsets (X,Y)-- [2:0-1-12,0-1-8], [6:0-2-4,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.33	Vert(LL) -0.02 in (loc) 6-7 l/defl >999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.19	Vert(CT) -0.03 6-7 >999		
TCDL 10.0	Rep Stress Incr NO	WB 0.02	Horz(CT) -0.00 6 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 23 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-6-9 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=346/0-7-6 (min. 0-1-8), 6=216/Mechanical
Max Horz 7=115(LC 9)
Max Uplift 7=-40(LC 10), 6=-76(LC 7)
Max Grav 7=346(LC 1), 6=233(LC 32)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-7=-306/53

NOTES- (11)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 6.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-2=-82, 2-3=-82, 3-4=-82, 5-7=-20
Concentrated Loads (lb)
Vert: 9=2(F=1, B=1)


Job Q104-179RT	Truss H01	Truss Type Hip Girder	Qty 1	Ply 2	BANDY RESIDENCE
-------------------	--------------	--------------------------	----------	----------	-----------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:04:45 2021 Page 1

-0-10-8 5-0-0 10-0-0 15-0-0 20-0-0 25-0-0 30-0-0 30-10-8
0-10-8 5-0-0 5-0-0 5-0-0 5-0-0 5-0-0 5-0-0 0-10-8

Scale = 1:58.3



0-0-8 5-0-0 10-0-0 15-0-0 20-0-0 25-0-0 29-11-8 30-0-0
0-0-8 4-11-8 5-0-0 5-0-0 5-0-0 5-0-0 4-11-8 0-0-8

Plate Offsets (X,Y)-- [4:0-2,0-0-1-4], [9:0-2-0,0-1-8], [17:0-2-12,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) Snow (Pf/Pg) 30.0 30.8/40.0	Plate Grip DOL Lumber DOL Rep Stress Incr Code IRC2015/TPI2014	2-0-0 1.15 1.15 NO	TC 0.82 BC 0.46 WB 0.37 Matrix-S	Vert(LL) -0.11 in (loc) 16 >999 L/d 240 Vert(CT) -0.18 16 >999 180 Horz(CT) 0.05 11 n/a n/a	MT20 197/144
TCDL BCLL BCDL					Weight: 319 lb FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x6 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x6 SPF No.2 3-2-0, Right 2x6 SPF No.2 3-2-0

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-10-14 oc purlins, except 2-0-0 oc purlins (5-8-9 max.): 4-9.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 2=2642/0-5-8 (min. 0-2-1), 11=2642/0-5-8 (min. 0-2-1)

Max Horz 2=83(LC 8)

Max Uplift2=273(LC 10), 11=-273(LC 10)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=3440/368, 3-4=3310/389, 4-19=-3924/442, 19-20=-3926/441, 20-21=-3927/442,

5-21=-3931/442, 5-22=-3926/441, 22-23=-3926/441, 23-24=-3926/441, 6-24=-3926/441,

6-25=-3929/442, 25-26=-3929/442, 7-26=-3929/442, 7-8=-3929/442, 8-27=-2392/315,

27-28=-2388/315, 28-29=-2387/315, 9-29=-2386/315, 9-10=-3306/388, 10-11=-3435/367

BOT CHORD 2-18=-239/2443, 18-30=-238/2433, 30-31=-238/2433, 17-31=-238/2433, 17-32=-381/4360,

32-33=-381/4360, 16-33=-381/4360, 15-16=-381/4360, 15-34=-381/4360,

34-35=-381/4360, 14-35=-381/4360, 14-36=-353/3929, 36-37=-353/3929,

13-37=-353/3929, 11-13=-216/2441

WEBS 4-18=-16/365, 4-17=-186/2064, 5-17=-795/203, 6-17=-605/51, 6-16=0/330,

6-14=-601/50, 8-14=0/626, 8-13=-2091/190, 9-13=-129/1720

NOTES- (16)

1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:

Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.

Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.

Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.

2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.

3) Unbalanced roof live loads have been considered for this design.

4) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

5) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

7) Provide adequate drainage to prevent water ponding.

8) All plates are 4x4 MT20 unless otherwise indicated.

9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	H01	Hip Girder	1	2	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:04:45 2021 Page 2

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-3PSLTHdwj4psrv5oB0pLwTZ2jp_tyjcpXo_F7hz474G

NOTES- (16)

- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=273, 11=273.
- 12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- 15) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 340 lb down and 111 lb up at 5-0-0, and 340 lb down and 111 lb up at 24-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 16) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-82, 4-9=-82, 9-12=-82, 2-11=-20


Concentrated Loads (lb)

Vert: 4=-105(F) 7=-105(F) 18=-340(F) 16=-29(F) 6=-105(F) 13=-340(F) 9=-105(F) 20=-105(F) 21=-105(F) 22=-105(F) 24=-105(F) 25=-105(F) 27=-105(F) 28=-105(F) 30=-29(F) 31=-29(F) 32=-29(F) 33=-29(F) 34=-29(F) 35=-29(F) 36=-29(F) 37=-29(F)

Job Q104-179RT	Truss H02	Truss Type Hip	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY		
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine							8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:39 2021 Page 1 ID:k67_5nOKmB2GQsoap?Ao4zlytl-VdD1RgNFXxNGXJt2HyUjOfljqR5NatRmsxPbTz477A

-0-10-8 7-0-0 15-0-0 23-0-0 30-0-0 30-10-8
0-10-8 7-0-0 8-0-0 8-0-0 7-0-0 0-10-8

Scale = 1:53.8



0-0-8 7-0-0 15-0-0 23-0-0 29-11-8 30-0-0
0-0-8 6-11-8 8-0-0 8-0-0 6-11-8 0-0-8

Plate Offsets (X,Y)-- [2:0-7-7,Edge], [4:0-3-0,0-1-8], [6:0-3-0,0-1-8], [8:0-7-7,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.69	Vert(LL) -0.11 12-14	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.73	Vert(CT) -0.22 12-14		
TCDL 10.0	Rep Stress Incr YES	WB 0.42	Horz(CT) 0.08 8		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 148 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E - 4-6-15, Right 2x8 SP 2400F 2.0E -Ø 4-6-15

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-9-13 oc purlins, except
2-0-0 oc purlins (5-9-13 max.); 4-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-14, 5-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1595/0-5-8 (min. 0-2-8), 8=1595/0-5-8 (min. 0-2-8)
Max Horz 2=112(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-15=-1921/49, 15-16=-1835/54, 3-16=-1768/57, 3-4=-1769/87, 4-17=-1310/125,
17-18=-1310/124, 5-18=-1312/124, 5-19=-1312/124, 19-20=-1310/124, 6-20=-1310/125,
6-7=-1769/87, 7-21=-1768/56, 21-22=-1835/54, 8-22=-1920/49

BOT CHORD 2-23=0/1363, 14-23=0/1363, 13-14=0/1932, 12-13=0/1932, 11-12=0/1932, 10-11=0/1932,
10-24=0/1309, 8-24=0/1309

WEBS 4-14=0/754, 5-14=-852/23, 5-12=0/367, 5-10=-852/23, 6-10=0/754

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 7-0-0, Exterior(2) 7-0-0 to 11-2-15, Interior(1) 11-2-15 to 23-0-0, Exterior(2) 23-0-0 to 27-2-15, Interior(1) 27-2-15 to 30-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE-BUDGET ONLY
Q104-179RT	H03	Hip	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-zpnPe0NuIVF69TSErf?ywSPTFEp964la?Vgz7vz4779

-0-10-8 4-7-12 | 9-0-0 | 15-0-0 | 21-0-0 | 25-4-4 | 30-0-0 | 30-10-8
0-10-8 4-7-12 | 4-4-4 | 6-0-0 | 6-0-0 | 4-4-4 | 4-7-12 | 0-10-8

Scale = 1:61.3



0-0-8	9-0-0	15-0-0	21-0-0	29-11-8	30-0-0
0-0-8	8-11-8	6-0-0	6-0-0	8-11-8	0-0-8

Plate Offsets (X,Y)-- [2:0-7-7,Edge], [5:0-3-0,0-1-8], [7:0-3-0,0-1-8], [10:0-7-7,Edge]

LUMBER-

TOP CHORD 2x4 SPF No.2

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

WEBS 2x4 SP 10.2
SLIDER Left 2x8 SP 2400F 2.0E -Ø 3-1-15,
Right 2x8 SP 2400F 2.0E -Ø 3-1-15

BRACING-

BRACING TOP CHORD

Structural wood sheathing directly applied or 3-2-8 oc purlins, except 2-0-0 oc purlins (4-8-15 max.): 5-7.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing
1 Row at midpt 6-15, 6-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1595/0-5-8 (min. 0-2-8), 10=1595/0-5-8 (min. 0-2-8)
Max Horz 2=141(LC 13)

FORCES. (lb) -

TOP CHORD	2-3=-1937/82, 3-4=-1804/104, 4-5=-1647/130, 5-16=-1202/134, 16-17=-1202/133, 6-17=-1205/133, 6-18=-1205/133, 18-19=-1202/133, 7-19=-1202/134, 7-8=-1647/130, 8-9=-1804/104, 9-10=-1937/82
BOT CHORD	2-15=-8/1308, 15-20=0/1462, 14-20=0/1462, 13-14=0/1462, 13-21=0/1462, 12-21=0/1462, 10-12=-4/1298
WEBS	5-15=-2/606, 6-15=-530/36, 6-14=0/310, 6-12=-530/36, 7-12=-2/606

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 9-0-0, Exterior(2) 9-0-0 to 13-2-15, Interior(1) 13-2-15 to 21-0-0, Exterior(2) 21-0-0 to 25-5-8, Interior(1) 25-5-8 to 30-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss H04	Truss Type Hip	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY		
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine							ID:k67_5nKOKmB2GQsoap?Ao4zlytl-R0KnrMOW3Ydznd1RPNWBTgxb2e8UrWSKE9QWgLz4778 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:41 2021 Page 1

-0-10-8 5-7-12 11-0-0
0-10-8 5-7-12 5-4-4
19-0-0 8-0-0 24-4-4
5-4-4 5-4-4 30-0-0
5-7-12 0-10-8

Scale = 1:58.6




Plate Offsets (X,Y)-- [2:0-7-7,Edge], [4:0-1-8,0-2-0], [5:0-3-11,Edge], [6:0-3-12,0-2-8], [7:0-1-8,0-2-0], [9:0-7-7,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.82	Vert(LL) -0.18 12-14	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.67	Vert(CT) -0.32 12-14		
TCDL 10.0	Rep Stress Incr YES	WB 0.28	Horz(CT) 0.06 9		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	n/a	Weight: 166 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
T2: 2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E -Ø 3-9-8, Right 2x8 SP 2400F 2.0E -Ø 3-9-8

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-6-1 oc purlins, except 2-0-0 oc purlins (4-2-11 max.): 5-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1595/0-5-8 (min. 0-2-8), 9=1595/0-5-8 (min. 0-2-8)
Max Horz 2=169(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-16=-1939/51, 3-16=-1805/52, 3-4=-1806/80, 4-17=-1572/113, 5-17=-1449/149,
5-18=-1115/155, 18-19=-1115/155, 19-20=-1115/155, 20-21=-1115/155, 6-21=-1115/155,
6-22=-1450/149, 7-22=-1572/113, 7-8=-1806/80, 8-23=-1805/52, 9-23=-1938/51
BOT CHORD 2-15=0/1328, 14-15=0/1328, 13-14=0/1137, 12-13=0/1137, 11-12=0/1315, 9-11=0/1315
WEBS 4-14=-292/100, 5-14=0/471, 6-12=0/403, 7-12=-292/100

NOTES- (10)


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2)-0-10-8 to 2-1-8, Interior(1) 2-1-8 to 11-0-0, Exterior(2) 11-0-0 to 15-2-15, Interior(1) 15-2-15 to 19-0-0, Exterior(2) 19-0-0 to 23-2-15, Interior(1) 23-2-15 to 30-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 10) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss H05	Truss Type Hip	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:42 2021 Page 1

-0-10-8 6-7-12 13-0-0 17-0-0 23-4-4 30-0-0 30-10-8
0-10-8 6-7-12 6-4-4 4-0-0 6-4-4 6-7-12 0-10-8



Scale = 1:75.0

0-0-8 6-7-12 13-0-0 17-0-0 23-4-4 29-11-8 30-0-0
0-0-8 6-7-4 6-4-4 4-0-0 6-4-4 6-7-4 0-0-8

Plate Offsets (X,Y)-- [2:0-7-7,Edge], [4:0-1-8,0-2-0], [6:0-3-4,0-1-4], [7:0-3-0,0-1-8], [9:0-1-8,0-2-0], [11:0-7-7,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.77	Vert(LL) -0.07 14-16	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.51	Vert(CT) -0.13 16-17		
TCDL 10.0	Rep Stress Incr YES	WB 0.19	Horz(CT) 0.06 11		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 180 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x8 SP 2400F 2.0E -Ø 4-5-5, Right 2x8 SP 2400F 2.0E -Ø 4-5-5

BRACING-

TOP CHORD

Structural wood sheathing directly applied or 2-2-0 oc purlins, except 2-0-0 oc purlins (5-8-10 max.): 6-7.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 4-16, 6-14, 9-14

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1595/0-5-8 (min. 0-2-8), 11=1595/0-5-8 (min. 0-2-8)
Max Horz 2=198(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-18-1927/40, 3-18-1797/44, 3-4-1788/77, 4-19-1468/124, 5-19-1304/143, 5-6-1290/167, 6-7-1002/171, 7-8-1289/167, 8-20-1305/143, 9-20-1469/124, 9-10-1782/77, 10-21-1790/44, 11-21-1922/40

BOT CHORD 2-22-0/1454, 17-22-0/1454, 17-23-0/1454, 16-23-0/1454, 16-24-0/1071, 15-24-0/1071, 14-15-0/1071, 14-25-0/1330, 13-25-0/1330, 13-26-0/1330, 11-26-0/1330

WEBS 4-17-0/315, 4-16-532/111, 6-16-18/540, 7-14-27/502, 9-14-532/111, 9-13-0/315

NOTES- (10)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B;

Enclosed; MWFRS (directional) and C-C Exterior(2)-0-10-8 to 2-1-8, Interior(1) 2-1-8 to 13-0-0, Exterior(2) 13-0-0 to 21-2-15, Interior(1) 21-2-15 to 30-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

5) Provide adequate drainage to prevent water ponding.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

10) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	J01	Jack-Open	11	1	
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					
8/120 S, Dec 30, 2020 MiTek Industries, Inc. Mon, Jun 21 09:05:35 2021 Page 1					

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:05:35 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-b1TFzNDlyS6mrawP6Wj3y0egNz6tgQvA1Z5utnz473U

-0-10-8	5-0-0
0-10-8	5-0-0

Scale = 1:30.2




Plate Offsets (X,Y)-- [2:0-1-8,0-1-8], [4:0-6-0,0-1-8]

LUMBER-

LUMBER-
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBs 2x4 SPF No.2

BRACING-

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS: (lb/size) 5=336/0-5-8 (min. 0-1-8) 3=187/Mechanical 4=49/Mechanical

Max Horz 5=133(LC 14)

Max | Δ lift| = 58 (L.C. 14)

Max Splits 3=38(LC 14)

FORCES (lb)

FORCES: (lb) - Max. Comp./Max. Tens. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-5=288/18

grip DOL=1.60
 2) TCLL: ASCE 7-10; $Pr=30.0 \text{ psf}$ (roof live load: Lumber DOL=1.15 Plate DOL=1.15); $Pg=40.0 \text{ psf}$ (ground snow); $Pf=30.8 \text{ psf}$ (flat

3) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs

4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

5) * This truss has been designed for a live load of 3:

will fit between the bottom chord and any other members.

- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.

8) This truss is designed in accorda

referenced standard ANSI/TPI 1

LOAD CASE(S): Standard

Job Q104-179RT	Truss J02	Truss Type Jack-Open	Qty 2	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

ID:k67_5nOKmB2GQsc
3-0-7
3-0-7

Scale = 1:20.8




Plate Offsets (X,Y)-- [2:0-1-8,0-1-8]

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEB 2x4 SPF No.2

BRACING-

ARCING TOP CHORD	Structural wood sheathing directly applied or 3-0-7 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. ((lb/size) 6=242/0-5-8 (min. 0-1-8). 3=100/Mechanical. 4=28/Mechanical

Max Horz 6=96(LC 14)

Max Fluz 0=30(LC 14)
Max Uplift3=-29(LC 14), 4=-8(LC 14)
Max Grav 6=242(LC 1), 3=100(LC 1), 4=57(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

NOTES: (9)

- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 2-11-11 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 3) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss J03	Truss Type Jack-Open	Qty 2	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:06:12 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-08CEk1gVEpnWnGFWnntkypg4Ctnzq8ldYqZMg8z472v

-0-10-8 1-0-7
0-10-8 1-0-7

Scale = 1:12.3




Plate Offsets (X,Y)-- [2:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.09	Vert(LL) 0.00 in (loc) 6 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.02	Vert(CT) -0.00 6 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.02	Horz(CT) -0.00 3 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 6 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-0-7 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=176/0-5-8 (min. 0-1-8), 3=-13/Mechanical, 4=9/Mechanical
Max Horz 6=31(LC 14)
Max Uplift 6=-8(LC 14), 3=-40(LC 18), 4=-29(LC 14)
Max Grav 6=176(LC 1), 3=16(LC 14), 4=20(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 3, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss J04	Truss Type Jack-Open	Qty 2	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:06:32 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-Q?Qowsv2XylhBLnMy_ERm1VVVxbsWBcZ8xPPN_z472b
-0-10-8 3-0-7 3-0-7
0-10-8

Scale = 1:20.8




Plate Offsets (X,Y)-- [2:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.13	Vert(LL) -0.00 in (loc) 5-6 l/defl >999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.07	Vert(CT) -0.01 5-6 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.02	Horz(CT) -0.00 3 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 13 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-0-7 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=242/0-5-8 (min. 0-1-8), 3=100/Mechanical, 4=28/Mechanical
Max Horz 6=96(LC 14)
Max Uplift 3=29(LC 14), 4=8(LC 14)
Max Grav 6=242(LC 1), 3=100(LC 1), 4=57(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 2-11-11 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss J05	Truss Type Jack-Open	Qty 2	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:06:51 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-Nf3_vM8z2oh_zGj0ZU4u12nlMb55TnPMWOWwYNz4721

-0-10-8 1-0-7
0-10-8 1-0-7

Scale = 1:12.3




Plate Offsets (X,Y)-- [2:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.09	Vert(LL) 0.00	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.02	Vert(CT) -0.00		
TCDL 10.0	Rep Stress Incr YES	WB 0.02	Horz(CT) -0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 6 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-0-7 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=176/0-5-8 (min. 0-1-8), 3=-13/Mechanical, 4=9/Mechanical
Max Horz 6=31(LC 14)
Max Uplift 6=-8(LC 14), 3=-40(LC 18), 4=-29(LC 14)
Max Grav 6=176(LC 1), 3=16(LC 14), 4=20(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 3, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard


Job Q104-179RT	Truss J06	Truss Type Jack-Open	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	-------------------------	----------	----------	-----------------------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:45 2021 Page 1

-0-10-8
0-10-8
2-0-15
2-0-15

Scale = 1:18.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.09	Vert(LL) 0.00	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.07	Vert(CT) -0.00		
TCDL 10.0	Rep Stress Incr YES	WB 0.00	Horz(CT) -0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-R			
BCDL 10.0				Weight: 8 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-0-15 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=201/0-5-8 (min. 0-1-8), 3=56/Mechanical, 4=16/Mechanical

Max Horz 5=91(LC 14)

Max Uplift 3=33(LC 14), 4=7(LC 14)

Max Grav 5=201(LC 1), 3=62(LC 20), 4=34(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 33 lb uplift at joint 3 and 7 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard


Job Q104-179RT	Truss J07	Truss Type Jack-Open	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	-------------------------	----------	----------	-----------------------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:45 2021 Page 1

-0-10-8
0-10-8
2-0-15
2-0-15

Scale = 1:18.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.09	Vert(LL) 0.00 in (loc) 5 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.07	Vert(CT) -0.00 4-5 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.00	Horz(CT) -0.00 3 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-R		Weight: 8 lb	FT = 10%
BCDL 10.0					

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-0-15 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=201/0-5-8 (min. 0-1-8), 3=56/Mechanical, 4=16/Mechanical

Max Horz 5=91(LC 14)

Max Uplift 3=33(LC 14), 4=7(LC 14)

Max Grav 5=201(LC 1), 3=62(LC 20), 4=34(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)


- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 33 lb uplift at joint 3 and 7 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss M01	Truss Type Monopitch	Qty 2	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:46 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-oz8gv4Set5GGtOvOCw6MAjfXxfwcWmXTNR7HLZz4773

-0-10-8 5-8-0 10-4-0
0-10-8 5-8-0 4-8-0

Scale: 3/16"=1'



0-0-8 5-8-0 6-1-12 10-4-0
0-0-8 5-7-8 0-5-12 4-2-4

Plate Offsets (X,Y)-- [3:0-1-4,0-1-8], [6:0-1-8,0-1-8], [9:Edge,0-10-9]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.49	Vert(LL) -0.03 in (loc) 8-9 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.35	Vert(CT) -0.07 8-9 >968 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.36	Horz(CT) -0.04 7 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 61 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 5-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=158/0-5-8 (min. 0-1-8), 7=945/0-5-4 (min. 0-1-9)

Max Horz 9=291(LC 11)

Max Uplift 9=-109(LC 12), 7=-325(LC 11)

Max Grav 9=363(LC 21), 7=1000(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-10=-723/687, 3-10=-682/735, 2-9=-545/446

BOT CHORD 8-9=-482/593, 3-7=-873/690

WEBS 3-6=-310/332, 2-8=-711/604

NOTES- (8)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-2-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 109 lb uplift at joint 9 and 325 lb uplift at joint 7.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____


LOAD CASE(S) Standard

Job Q104-179RT	Truss M01G	Truss Type GABLE	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

-0-10-8 5-8-0 10-4-0
0-10-8 5-8-0 4-8-0

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-VVmElcVCZEC1le3ec5B_DikPzV3JEdQTYebV1o23jFo
8,420 s Dec 30 2020 MiTek Industries, Inc. Tue Jun 22 14:27:23 2021 Page 1

Scale: 3/16"=1"



0-0-8 5-8-0 6-1-12 10-4-0
0-0-8 5-7-8 0-5-12 4-2-4

Plate Offsets (X,Y)-- [6:0-1-8,0-1-8], [10:0-3-0,0-2-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.45	Vert(LL) -0.03 in (loc) 9-10 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.33	Vert(CT) -0.07 in 9-10 >948 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.87	Horz(CT) -0.04 in 7 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 86 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing, Except: 10-0-0 oc bracing: 8-9.
WEBS 1 Row at midpt 5-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=907/0-5-4 (min. 0-1-9), 10=163/0-5-8 (min. 0-1-8), 7=33/0-5-4 (min. 0-1-9)

Max Horz 10=291(LC 11)

Max Uplift 8=-339(LC 11), 10=-102(LC 12), 7=-70(LC 15)

Max Grav 8=971(LC 20), 10=370(LC 21), 7=141(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-20=-338/180, 3-20=-288/209, 2-10=-421/209

BOT CHORD 3-8=-975/758

WEBS 3-6=-296/329, 3-10=-821/969

NOTES- (11)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2)-0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-2-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 339 lb uplift at joint 8, 102 lb uplift at joint 10 and 70 lb uplift at joint 7.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss M02	Truss Type Monopitch	Qty 4	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

-0-10-8 5-5-4
0-10-8 5-5-4 | 10-4-0
4-10-12

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:09:46 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-J88eCGkrZk9T9ceJkjwdyXXA8nazlZ7i7PhBkz47?Z

Scale = 1:60.8




Plate Offsets (X,Y)-- [2:0-7-1,Edge], [4:0-1-4,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.60	Vert(LL) -0.03 in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.25	Vert(CT) -0.06 2-8 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.77	Horz(CT) 0.03 7 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 69 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E 4-1-4

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 9-1-3 oc bracing.
WEBS 1 Row at midpt 6-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=507/Mechanical, 2=597/0-5-8 (min. 0-1-8)

Max Horz 2=298(LC 11)
Max Uplift 7=123(LC 11)
Max Grav 7=538(LC 20), 2=597(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-9=-738/0, 3-9=-638/0, 3-4=-478/1
BOT CHORD 2-8=-399/688, 7-8=-384/677
WEBS 4-8=-261/674, 4-7=-777/399

NOTES- (10)

- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-2-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 3) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=123.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss M03	Truss Type Monopitch	Qty 4	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:25:27 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-Hx1piwD8Qnsrl0FOqwhpAY6gAeflRhmWy6vS31z45uc
-0-10-8 1-8-8 2-0-0
0-10-8 1-8-8 0-3-8

Scale = 1:18.2




Plate Offsets (X,Y)-- [2:0-1-4,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.09	Vert(LL) -0.00	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.03	Vert(CT) -0.00		
TCDL 10.0	Rep Stress Incr YES	WB 0.02	Horz(CT) -0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 12 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=195/0-5-8 (min. 0-1-8), 4=62/0-1-8 (min. 0-1-8)

Max Horz 5=79(LC 11)

Max Uplift 5=14(LC 14), 4=45(LC 11)

Max Grav 5=195(LC 1), 4=82(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (10)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss M04	Truss Type Monopitch	Qty 2	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:21:54 2021 Page 1

-0-10-8 2-1-11 2-5-3
0-10-8 2-1-11 0-3-8

Scale = 1:20.3




Plate Offsets (X,Y)-- [2:0-1-4,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.09	Vert(LL) -0.00 in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.04	Vert(CT) -0.00 4-5 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.03	Horz(CT) -0.00 4 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 14 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-5-3 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=89/Mechanical, 5=212/0-5-8 (min. 0-1-8)

Max Horz 5=91(LC 11)
Max Uplift 4=48(LC 11), 5=13(LC 14)
Max Grav 4=108(LC 20), 5=212(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 3) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 5.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss M05	Truss Type Monopitch	Qty 5	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Tue Jun 22 14:27:57 2021 Page 1
ID:k67_5nOKmB2GQsoap?Ao4zlytl-V2p4uEwXZgUDqsfAcEoycs9FKCcqB9NTNxqlEpz3jFG

-0-10-8 4-9-9 9-1-0
0-10-8 4-9-9 4-3-7

Scale = 1:21.2




Plate Offsets (X,Y)-- [2:0-3-9,0-1-8], [4:0-2-13,0-1-0], [5:0-2-12,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.33	Vert(LL) -0.20	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.61	Vert(CT) -0.40		
TCDL 10.0	Rep Stress Incr YES	WB 0.26	Horz(CT) 0.01		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	(loc) 2-5		
BCDL 10.0			>532	240	
			>263	180	
			5	n/a	n/a
				Weight: 31 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=437/0-3-8 (min. 0-1-8), 2=538/0-5-8 (min. 0-1-8)

Max Horz 2=85(LC 15)
Max Uplift 2=17(LC 16)
Max Grav 5=506(LC 21), 2=561(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-6=781/72, 3-6=741/87
BOT CHORD 2-5=146/704
WEBS 3-5=700/135

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2)-0-10-8 to 2-1-8, Interior(1) 2-1-8 to 8-11-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 2.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S01	Truss Type Scissor	Qty 6	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	-----------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:13:08 2021 Page 1

-0-10-8 5-6-12 10-10-0 14-10-0 20-1-4 25-8-0 26-6-8
0-10-8 5-6-12 5-3-4 4-0-0 5-3-4 5-6-12 0-10-8

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-qALV1GIRGdBVic2T89LlpYv_eZemlGOrcYKMH1z46yP




Plate Offsets (X,Y)-- [2:0-7-1,Edge], [4:0-1-4,0-2-0], [6:0-4-4,0-1-12], [7:0-4-4,0-1-12], [9:0-1-4,0-2-0], [11:0-7-1,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.89	Vert(LL) -0.15 in (loc) 15 >999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.57	Vert(CT) -0.25 13-14 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.17	Horz(CT) 0.33 11 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 147 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
T1,T5: 2x4 SPF 2100F 1.8E

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x8 SP 2400F 2.0E 4-2-5, Right 2x8 SP 2400F 2.0E 4-2-5

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (4-7-10 max.): 6-7.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing
be installed during truss erection, in accordance with Stabilizer
Installation guide.

REACTIONS. (lb/size) 2=1373/0-5-8 (min. 0-1-13), 11=1373/0-5-8 (min. 0-1-13)
Max Horz 2=207(LC 13)
Max Uplift2=4(LC 14), 11=4(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-18=-2468/0, 3-18=-2305/0, 3-4=-2304/22, 4-19=-1935/0, 5-19=-1853/0, 5-6=-1830/25,
6-20=-1519/18, 20-21=-1519/18, 7-21=-1519/18, 7-8=-1830/27, 8-22=-1853/0,
9-22=-1935/0, 9-10=-2304/0, 10-23=-2305/0, 11-23=-2468/0

BOT CHORD 2-17=0/1690, 16-17=0/1705, 15-16=0/1429, 14-15=0/1429, 13-14=0/1701, 11-13=0/1684
WEBS 4-16=-298/160, 6-16=-57/304, 6-15=0/675, 7-15=0/712, 7-14=-57/304, 9-14=-297/161

NOTES- (12)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=26ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2)-0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-10-0, Exterior(2) 10-10-0 to 19-0-15, Interior(1) 19-0-15 to 26-6-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Bearing at joint(s) 2, 11 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 11.
- 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 12) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss S01G	Truss Type GABLE	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:13:34 2021 Page 1

-0-10-8 5-6-12 10-10-0 14-10-0 20-1-4 25-8-0 26-6-8
0-10-8 5-6-12 5-3-4 4-0-0 5-3-4 5-6-12 0-10-8

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-3BwKV90l8dTpB1TgcpOs1zR42WsO0qgBdkBWz46y?

Scale = 1:66.2




Plate Offsets (X,Y)-- [2:0-7-1,Edge], [4:0-1-4,0-2-0], [6:0-4-4,0-1-12], [7:0-4-4,0-1-12], [9:0-1-4,0-2-0], [11:0-7-1,Edge], [15:0-1-12,0-1-8], [19:0-1-9,0-1-0], [22:0-1-9,0-1-0], [31:0-1-9,0-1-0], [34:0-1-9,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.89	Vert(LL) -0.15 (loc) 15 >999 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.57	Vert(CT) -0.25 13-14 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.17	Horz(CT) 0.33 11 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 183 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
T1,T5: 2x4 SPF 2100F 1.8E

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

OTHERS 2x4 SPF No.2

SLIDER Left 2x8 SP 2400F 2.0E 4-2-5, Right 2x8 SP 2400F 2.0E 4-2-5

BRACING-

TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (4-7-10 max.); 6-7.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1373/0-5-8 (min. 0-1-13), 11=1373/0-5-8 (min. 0-1-13)

Max Horz 2=207(LC 13)

Max Uplift 2=-4(LC 14), 11=-4(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-39=-2468/0, 3-39=-2305/0, 3-4=-2304/22, 4-40=-1935/0, 5-40=-1853/0, 5-6=-1830/25,
6-41=-1519/18, 41-42=-1519/18, 7-42=-1519/18, 7-8=-1830/27, 8-43=-1853/0,

9-43=-1935/0, 9-10=-2304/0, 10-44=-2305/0, 11-44=-2468/0

BOT CHORD 2-17=0/1690, 16-17=0/1705, 15-16=0/1429, 14-15=0/1429, 13-14=0/1701, 11-13=0/1684

WEBS 4-16=-298/160, 6-16=-57/304, 6-15=0/675, 7-15=0/712, 7-14=-57/304, 9-14=-297/161

NOTES- (15)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=26ft; eave=4ft; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-10-0, Exterior(2) 10-10-0 to 19-0-15,
Interior(1) 19-0-15 to 26-6-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces
& MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry
Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat
roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs
non-concurrent with other live loads.

6) Provide adequate drainage to prevent water ponding.

7) All plates are 2x4 MT20 unless otherwise indicated.

8) Gable studs spaced at 2-0-0 oc.

9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide
will fit between the bottom chord and any other members.

11) Bearing at joint(s) 2, 11 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify
capacity of bearing surface.

12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 11.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	S01G	GABLE	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:13:34 2021 Page 2
ID:k67_5nOKmB2GQsoap?Ao4zlytl-3BwKV90l8dTppB1TgcpOs1zR42WsO0qgBbdkBWz46y?

NOTES- (15)

13) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

15) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S02	Truss Type Scissor	Qty 6	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:51 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-9xxZynWnriduZz9oM_ThXtnMKNgboB1ICXjr20mz477

-0-10-8 2-6-0 5-6-0 8-6-0 10-6-0 12-6-0 15-6-0 18-6-0 21-0-0 21-10-8
0-10-8 2-6-0 3-0-0 3-0-0 2-0-0 2-0-0 3-0-0 3-0-0 2-6-0 0-10-8

Scale: 3/16"=1"




Plate Offsets (X,Y)-- [2:0-7-1,Edge], [4:0-1-4,0-1-8], [5:0-1-4,0-1-8], [7:0-1-4,0-1-8], [9:0-1-4,0-1-8], [11:0-1-4,0-1-8], [12:0-1-4,0-1-8], [14:0-7-1,Edge], [16:0-2-12,0-3-4], [17:0-3-0,0-3-4], [18:0-3-0,0-1-8], [19:0-4-0,0-3-8], [20:0-3-0,0-1-8], [21:0-3-0,0-3-4], [22:0-2-12,0-3-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.71	in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.48	Vert(LL) -0.08 20 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.36	Vert(CT) -0.13 20 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.16 14 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 149 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x6 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x6 SPF No.2 -Ø 2-0-12, Right 2x6 SPF No.2 -Ø 2-0-12

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 3-0-7 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1133/0-5-8 (min. 0-1-8), 14=1133/0-5-8 (min. 0-1-8)
Max Horz 2=200(LC 12)
Max Uplift2=10(LC 14), 14=-10(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1733/0, 3-23=-1677/0, 4-23=-1622/0, 4-5=-1600/12, 5-6=-1274/44, 6-7=-1166/55,

7-8=-991/105, 8-9=-991/103, 9-10=-1166/53, 10-11=-1274/41, 11-12=-1600/8,

12-24=-1609/0, 13-24=-1677/0, 13-14=-1733/0

BOT CHORD 2-22=-43/1187, 21-22=-26/1184, 20-21=0/1146, 19-20=0/839, 18-19=0/830,

17-18=0/1125, 16-17=0/1111, 14-16=0/1093

WEBS 8-19=-109/1139, 9-19=-502/83, 9-18=0/486, 11-18=-423/62, 11-17=0/271, 7-19=-521/82,

7-20=0/504, 5-20=-439/61, 5-21=0/304

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-6-0, Exterior(2) 10-6-0 to 13-6-0, Interior(1) 13-6-0 to 21-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 2, 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 14.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	S02G	GABLE	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8,420 s Dec 30 2020 MiTek Industries, Inc. Tue Jun 22 14:33:27 2021 Page 2
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-rYlr94vXr43OPaubxXjL_SpZ6EG6WNQ2FHmmqh23jA6

NOTES- (13)

12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
13) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:23:43 2021 Page 1

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:23:43 2021 Page 1
PSCC-2020-2A-1-h-14-D7-1DQ111-PON-5W-25E00017-Y01-R1 ID:fc21-18-11

ID:R67_5nKUKmbZGQsoap-A04zly
-0-10-8 2-6-0 | 5-6-0 | 8-6-0 | 10-6-0 | 12-6-0 | 15-6-0 | 18-3-8 18-5-0
0-10-8 2-6-0 | 3-0-0 | 3-0-0 | 2-0-0 | 2-0-0 | 3-0-0 | 2-9-8 0-1-8

$$4 \times 4 =$$

Scale = 1:70.1




Plate Offsets (X,Y)-- [2:0-5-0,0-2-10], [4:0-1-4,0-1-8], [5:0-1-4,0-1-8], [7:0-1-4,0-1-8], [9:0-1-4,0-1-8], [10:0-1-4,0-1-8], [11:0-1-4,0-1-8], [12:0-3-3,0-0-12], [13:0-3-0,0-3-8], [14:0-3-0,0-1-8], [15:0-4-0,0-3-8], [16:0-3-0,0-1-8], [17:0-3-0,0-3-4], [18:0-3-0,0-3-4]

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 3-8-6 oc purlins, except end verticals.
BOT CHORD 2x6 SPF No.2	
WEBS 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 12-13.
SLIDER Left 2x6 SPF No.2 2-0-12	

REACTIONS. (lb/size) 2=1007/0-5-8 (min. 0-1-8), 12=915/0-1-8 (min. 0-1-8)
Max Horz 2=203(LC 13)
Max Uplift2=-10(LC 14)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3-1508/76, 3-19-1449/84, 4-19-1394/94, 4-5-1349/91, 5-6-1032/96, 6-7-925/107, 7-8-765/146, 8-9-768/151, 9-20-805/114, 10-20-912/92, 10-11-893/58, 11-12-878/54
BOT CHORD	2-18-145/1034, 17-18-133/1029, 16-17-56/963, 15-16-3/672, 14-15-0/581, 13-14-30/603
WEBS	5-17-19/287, 5-16-419/92, 7-16-43/473, 7-15-506/116, 8-15-172/832, 9-15-262/92, 10-13-254/36, 11-13-4/619

NOTES- (12)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-6-0, Exterior(2) 10-6-0 to 13-6-0, Interior(1) 13-6-0 to 18-3-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

5) All plates are MT20 plates unless otherwise indicated.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

8) Bearing at joint(s) 2, 12 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

9) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 12.

10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.

11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	S03	SCISSORS	6	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:23:44 2021 Page 2
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-CXnxWkPOU2JF?xgiPkIRbfEkhxk_JsyTSVO0bAz46oT

12) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S04	Truss Type Scissor	Qty 2	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:24:13 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-s61ucflafyz8zO0HcJmEGnxfbealc_3k7Vw27_z46o0

-0-10-8 4-9-12 | 9-4-0 4-6-4 | 13-10-4 4-6-4 | 18-8-0 4-9-12 | 19-6-8 0-10-8

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-s61ucflafyz8zO0HcJmEGnxfbealc_3k7Vw27_z46o0

Scale = 1:61.3

4x4 =




Plate Offsets (X,Y)-- [2:0-7-1,Edge], [5:0-2-0,0-1-12], [8:0-7-1,Edge], [10:0-4-0,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.71	Vert(LL) -0.24	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.67	Vert(CT) -0.49		
TCDL 10.0	Rep Stress Incr YES	WB 0.29	Horz(CT) 0.18		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	(loc) 2-10		
BCDL 10.0			l/defl >930	240	
			l/defl >453	180	
			l/defl n/a	n/a	
				Weight: 96 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E 3-8-2, Right 2x8 SP 2400F 2.0E 3-8-2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-1-9 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1017/0-5-8 (min. 0-1-8), 8=1017/0-5-8 (min. 0-1-8)
Max Horz 2=179(LC 12)
Max Uplift 2=9(LC 14), 8=9(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3-1624/11, 3-4-1483/35, 4-11-1231/0, 5-11-1137/0, 5-12-1137/0, 6-12-1231/0,
6-7-1483/33, 7-8-1624/9

BOT CHORD 2-10-27/1139, 8-10-0/1105
WEBS 5-10-0/1183

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 9-4-0, Exterior(2) 9-4-0 to 12-4-0, Interior(1) 12-4-0 to 19-6-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 2, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S05	Truss Type SCISSORS	Qty 2	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:26:15 2021 Page 1

ID:k67_5nOKmB2GQsoap?Ao4zlyt-HaP0D

Scale = 1:62.8

$$4 \times 4 =$$




Plate Offsets (X,Y)-- [2:0-2-0,0-1-4], [3:0-1-12,0-2-0], [4:0-2-0,0-1-12], [5:0-1-12,0-2-0], [7:0-2-4,0-2-0], [8:0-4-0,0-3-8]

LUMBER-

TOP CHORD 2x4 SPF No.2

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

WEBS 2X4 CPT N3.2
SLIDER Left 2x8 SP 2400F 2.0E 3-8-2

BRACING-

DRAGONS **TOP CHORD** Structural wood sheathing directly applied or 4-11-5 oc purlins, except end verticals.

BOT CHORD WEBS	except 3rd verticals. Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 5-7, 3-9
---------------------------	---

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (

REACTOR: (3/3.20) T=324.0°C (min. 313), S=1000/3.0°C (min. 313)
Max Horz 9=198(LC 13)

Max Flot 5=158(LC 15)

Max Spins = $\delta(\mathbb{E} S + 1)$

FORCES. (lb.) TOP CHORD.

TOP CHORD 2-10=-436/70, 3-10=-330/91, 3-11=-1249/0, 4-11=-152/1
5-12=-1247/5, 6-13=-351/40, 6-7=-330/59, 2-9=-483/100

BOT CHORD 3-12=-1247/3, 6-13=-331/40, 8-7=-330/35, 2-9=-483/114
WEBS 8-9=-62/1153, 7-8=-31/1103
4-8=0/1210, 5-7=-1252/26, 3-9=-1189/0

12-4-0 to 18-3-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFR for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; $Pr=30.0 \text{ psf}$ (roof live load: Lumber DOL=1.15 Plate DOL=1.15); $Pg=40.0 \text{ psf}$ (ground snow); $Pf=30.8 \text{ psf}$ (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; $Ct=1.10$

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

7) Bearing at joint(s) 7, 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9.

9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S06	Truss Type SCISSORS	Qty 2	Ply 1	BANDY RESIDENCE Job Reference (optional)
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:26:41 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlylI-XbzrgGYPpQc8k8ijHPQyG_43cl5ClwlW9XntJPZ46li

4-9-8 9-3-8 13-8-8 18-5-0
4-9-8 4-6-0 4-5-0 4-8-8

4x4 =

Scale = 1:62.7




Plate Offsets (X,Y)-- [2:0-1-12,0-2-0], [3:0-2-0,0-1-12], [4:0-1-12,0-2-0], [6:0-2-4,0-2-0], [7:0-4-0,0-3-8], [8:0-2-8,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.31	Vert(LL) -0.24	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.68	Vert(CT) -0.49		
TCDL 10.0	Lumber DOL 1.15	WB 0.32	Horz(CT) 0.14		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S			
BCDL 10.0	Code IRC2015/TPI2014			Weight: 88 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-0-3 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 2-8, 4-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=921/0-5-8 (min. 0-1-8), 6=921/0-3-8 (min. 0-1-8)
Max Horz 8=185(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-9=-384/35, 2-9=-278/57, 2-10=-1251/0, 3-10=-1105/25, 3-11=-1105/39, 4-11=-1247/4,

5-12=-350/40, 1-8=-355/56, 5-6=-330/59

BOT CHORD 7-8=-61/1158, 6-7=-31/1104

WEBS 3-7=0/1215, 2-8=-1243/22, 4-6=-1253/26

NOTES- (8)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 9-3-8, Exterior(2) 9-3-8 to 12-3-8, Interior(1) 12-3-8 to 18-3-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) Bearing at joint(s) 8, 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S06G	Truss Type Scissor Structural Gable	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:01:58 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-SHsDQAbA3mmZJEqvRJAf9dtUxFKCAE8J1vlsz476t

4-9-8 9-3-8 13-8-8 18-5-0
4-9-8 4-6-0 4-5-0 4-8-8

Scale = 1:60.6




Plate Offsets (X,Y)-- [2:0-1-12,0-2-0], [3:0-2-0,0-1-12], [4:0-1-12,0-2-0], [6:0-2-4,0-2-0], [7:0-4-0,0-3-8], [8:0-2-8,0-1-12], [9:0-1-9,0-1-0], [18:0-1-9,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.31	Vert(LL) -0.24	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.68	Vert(CT) -0.49		
TCDL 10.0	Lumber DOL 1.15	WB 0.32	Horz(CT) 0.14		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S			
BCDL 10.0	Code IRC2015/TPI2014			Weight: 107 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-0-3 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 2-8, 4-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=921/0-5-8 (min. 0-1-8), 6=921/0-3-8 (min. 0-1-8)
Max Horz 8=185(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-23=-384/35, 2-23=-278/57, 2-24=-1251/0, 3-24=-1105/25, 3-25=-1105/39,
4-25=-1247/4, 5-26=-350/40, 1-8=-355/56, 5-6=-330/59

BOT CHORD 7-8=-61/1158, 6-7=-31/1104
WEBS 3-7=0/1215, 2-8=-1243/22, 4-6=-1253/26

NOTES- (11)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 9-3-8, Exterior(2) 9-3-8 to 12-3-8, Interior(1) 12-3-8 to 18-3-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Cable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 9) Bearing at joint(s) 8, 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S07	Truss Type SCISSORS	Qty 8	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:29:46 2021 Page 1

5-2-12 10-2-0 18-2-0 23-1-4 28-4-0 29-2-8
5-2-12 4-11-4 8-0-0 4-11-4 5-2-12 0-10-8
ID:k67_5nKOKmB2GQsoap?Ao4zlyl-cAenVWnSEGwuQaLHclFKF?EZQtA38Vkhp5AlBz46ip




Plate Offsets (X,Y)-- [1:Edge,0-1-12], [2:0-1-12,0-1-8], [3:0-3-9,0-2-8], [4:0-3-9,0-2-8], [5:0-1-12,0-1-8], [6:0-3-0,0-1-4], [8:0-2-12,Edge], [10:0-3-0,0-2-12], [12:0-2-12,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.72	Vert(LL) -0.28 in (loc) 8-9 >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.84	Vert(CT) -0.58 8-9 >577 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.66	Horz(CT) 0.37 8 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 141 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*

T2: 2x6 SPF No.2

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x8 SP 2400F 2.0E 3-11-10, Right 2x8 SP 2400F 2.0E 3-11-10

BRACING-

TOP CHORD

Structural wood sheathing directly applied or 3-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-4-2 max.): 3-4.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 2-12, 5-8

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 12=1423/0-5-8 (min. 0-1-14), 8=1509/0-5-8 (min. 0-2-0)

Max Horz 12=-217(LC 12)

Max Uplift 8=-2(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-13=-488/50, 2-13=-341/74, 2-14=-2395/0, 3-14=-2246/18, 3-15=-2388/0, 15-16=-2388/0, 16-17=-2388/0, 17-18=-2388/0, 4-18=-2388/0, 4-19=-2244/0, 5-19=-2390/0, 5-20=-429/115, 6-20=-566/90, 1-12=-441/70, 6-8=-591/132

BOT CHORD 11-12=-22/1949, 10-11=0/1771, 9-10=0/1770, 8-9=0/1932
WEBS 3-11=-12/355, 3-10=0/1131, 4-10=0/1132, 4-9=-14/353, 2-12=-2264/13, 5-8=-2172/0

NOTES- (12)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=28ft; eave=4ft; Cat. II; Exp B;

Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 10-2-0, Exterior(2) 10-2-0 to 14-4-15, Interior(1) 14-4-15 to 18-2-0, Exterior(2) 18-2-0 to 22-4-15, Interior(1) 22-4-15 to 29-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

5) Provide adequate drainage to prevent water ponding.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

8) Bearing at joint(s) 12, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8.

10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

12) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss S07G	Truss Type GABLE	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:30:23 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-1OmGAEfXeaeMFgOH1P?FoGu5npjJeuBC4Yd6Yz46iE
5-2-12 10-2-0 18-2-0 23-1-4 28-4-0 29-2-8
5-2-12 4-11-4 8-0-0 4-11-4 5-2-12 0-10-8




Plate Offsets (X,Y)-- [1:Edge,0-1-12], [2:0-1-12,0-1-8], [3:0-3-9,0-2-8], [4:0-3-9,0-2-8], [5:0-1-12,0-1-8], [6:0-3-0,0-1-4], [8:0-2-12,Edge], [10:0-3-0,0-0-2], [10:0-3-0,0-2-12], [12:0-2-12,Edge], [17:0-1-9,0-1-0], [20:0-1-9,0-1-0], [32:0-1-9,0-1-0], [35:0-1-9,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.72	Vert(LL) -0.28	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.84	Vert(CT) -0.58		
TCDL 10.0	Lumber DOL 1.15	WB 0.66	Horz(CT) 0.37		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S			
BCDL 10.0	Code IRC2015/TPI2014			Weight: 181 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
T2: 2x6 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E 3-11-10, Right 2x8 SP 2400F 2.0E 3-11-10

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-4-2 max.); 3-4.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 2-12, 5-8

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 12=1423/0-5-8 (min. 0-1-14), 8=1509/0-5-8 (min. 0-2-0)
Max Horz 12=-217(LC 12)
Max Uplift 8=-2(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-40=-488/50, 2-40=-341/74, 2-41=-2395/0, 3-41=-2246/18, 3-42=-2388/0,
42-43=-2388/0, 43-44=-2388/0, 44-45=-2388/0, 4-46=-2244/0,
5-46=-2390/0, 5-47=-429/115, 6-47=-566/90, 1-12=-441/70, 6-8=-591/132

BOT CHORD 11-12=-22/1949, 10-11=0/1771, 9-10=0/1770, 8-9=0/1932
WEBS 3-11-12/355, 3-10=0/1131, 4-10=0/1132, 4-9=-14/353, 2-12=-2264/13, 5-8=-2172/0

NOTES- (15)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=28ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 10-2-0, Exterior(2) 10-2-0 to 14-4-15, Interior(1) 14-4-15 to 18-2-0, Exterior(2) 18-2-0 to 22-4-15, Interior(1) 22-4-15 to 29-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 6) Provide adequate drainage to prevent water ponding.
- 7) All plates are 2x4 MT20 unless otherwise indicated.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 11) Bearing at joint(s) 12, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	S07G	GABLE	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:30:24 2021 Page 2
ID:k67_5nOKmB2GQsoap?Ao4zlylI-VUx9TWFHlxjV_PFarkwEo0p3rB9y2h8LRkIAe_z46iD

NOTES- (15)

13) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

15) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S08	Truss Type SCISSORS	Qty 9	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:30:55 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlyl-5Sjt_6dk_Tc6CA6X9l_WYYbMzhkCoiovZ2lJdhz46hk

5-2-12 10-2-0 18-2-0 23-1-4 28-4-0
5-2-12 4-11-4 8-0-0 4-11-4 5-2-12

Scale = 1:67.0




Plate Offsets (X,Y)-- [2:0-1-12,0-1-8], [3:0-3-9,0-2-8], [4:0-3-9,0-2-8], [5:0-1-12,0-1-8], [7:0-2-12,Edge], [9:0-3-0,0-2-12], [11:0-2-12,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.72	Vert(LL) -0.28 in (loc) 7-8 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.84	Vert(CT) -0.58 10-11 >577		
TCDL 10.0	Rep Stress Incr YES	WB 0.66	Horz(CT) 0.38 7 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 139 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*

T2: 2x6 SPF No.2

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x8 SP 2400F 2.0E 3-11-10, Right 2x8 SP 2400F 2.0E 3-11-10

BRACING-

TOP CHORD

Structural wood sheathing directly applied or 3-4-13 oc purlins, except end verticals, and 2-0-0 oc purlins (3-3-14 max.): 3-4.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 2-11, 5-7

WEBS

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 11=1425/0-5-8 (min. 0-1-14), 7=1425/0-5-8 (min. 0-1-14)
Max Horz 11=-205(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-12=-488/51, 2-12=-341/75, 2-13=-2399/28, 3-13=-2250/67, 3-14=-2393/21, 14-15=-2393/21, 15-16=-2393/21, 16-17=-2393/21, 4-17=-2393/21, 4-18=-2250/68, 5-18=-2399/29, 5-19=-333/78, 6-19=-488/54, 1-11=-442/71, 6-7=-442/73

BOT CHORD 10-11=-70/1951, 9-10=0/1774, 8-9=0/1774, 7-8=-48/1951
WEBS 3-10=-9/355, 3-9=0/1134, 4-9=0/1134, 4-8=-12/355, 2-11=-2267/57, 5-7=-2267/45

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=28ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 10-2-0, Exterior(2) 10-2-0 to 14-4-15, Interior(1) 14-4-15 to 18-2-0, Exterior(2) 18-2-0 to 22-4-15, Interior(1) 22-4-15 to 28-2-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) Provide adequate drainage to prevent water ponding.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 11, 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 10) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss S09	Truss Type SCISSORS	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional)

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:31:25 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-CD7CHN_YwhOronPlv2WYmtqURnzDqHFJSjZvHyz46hG

5-2-12 10-2-0 18-2-0 23-1-4 28-4-0 29-2-8
5-2-12 4-11-4 8-0-0 4-11-4 5-2-12 0-10-8




Plate Offsets (X,Y)-- [1:Edge,0-1-12], [2:0-1-12,0-1-8], [3:0-3-9,0-2-8], [4:0-3-9,0-2-8], [5:0-1-12,0-1-8], [6:0-3-0,0-1-4], [8:0-2-12,Edge], [10:0-3-0,0-2-12], [12:0-2-12,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.72	Vert(LL) -0.28 in (loc) 8-9 >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.84	Vert(CT) -0.58 8-9 >577 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.66	Horz(CT) 0.37 8 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 141 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*

T2: 2x6 SPF No.2

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x8 SP 2400F 2.0E 3-11-10, Right 2x8 SP 2400F 2.0E 3-11-10

BRACING-

TOP CHORD

Structural wood sheathing directly applied or 3-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-4-2 max.): 3-4.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 2-12, 5-8

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 12=1423/0-5-9 (min. 0-1-14), 8=1509/0-5-8 (min. 0-2-0)

Max Horz 12=-217(LC 12)

Max Uplift 8=-2(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-13=-488/50, 2-13=-341/74, 2-14=-2395/0, 3-14=-2246/18, 3-15=-2388/0, 15-16=-2388/0, 16-17=-2388/0, 17-18=-2388/0, 4-18=-2388/0, 4-19=-2244/0, 5-19=-2390/0, 5-20=-429/115, 6-20=-566/90, 1-12=-441/70, 6-8=-591/132

BOT CHORD 11-12=-22/1949, 10-11=0/1771, 9-10=0/1770, 8-9=0/1932
WEBS 3-11=-12/355, 3-10=0/1131, 4-10=0/1132, 4-9=-14/353, 2-12=-2264/13, 5-8=-2172/0

NOTES- (12)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=28ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 10-2-0, Exterior(2) 10-2-0 to 14-4-15, Interior(1) 14-4-15 to 18-2-0, Exterior(2) 18-2-0 to 22-4-15, Interior(1) 22-4-15 to 29-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

5) Provide adequate drainage to prevent water ponding.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

8) Bearing at joint(s) 12, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8.

10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

12) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss S10	Truss Type SCISSOR GIRDER	Qty 7	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	------------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:32:16 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-D1jU_pbYvMqcQdp6PFxVLeRCYKT7HMuqB9Q6ZUz46gT

-0-10-8 5-2-12 10-2-0 4-11-4 18-2-0 8-0-0 23-1-4 4-11-4 28-4-0 5-2-12 29-2-8
0-10-8 5-2-12 4-11-4 8-0-0 4-11-4 5-2-12 0-10-8

Scale = 1:57.4




Plate Offsets (X,Y)-- [2:0-2-8,0-2-0], [3:0-1-12,0-1-12], [4:0-3-9,0-2-8], [5:0-3-9,0-2-8], [6:0-1-12,0-1-12], [7:0-2-8,0-2-0], [11:0-3-0,0-3-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.72	Vert(LL) -0.15 in (loc) 11 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.46	Vert(CT) -0.24 in 11 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.59	Horz(CT) 0.31 in 9 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 161 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*

T2: 2x6 SPF No.2

BOT CHORD 2x6 SPF No.2

WEBS 2x4 SPF No.2

SLIDER Left 2x6 SPF No.2 3-10-0, Right 2x6 SPF No.2 3-10-0

BRACING-

TOP CHORD

Structural wood sheathing directly applied or 3-3-12 oc purlins, except end verticals, and 2-0-0 oc purlins (3-3-10 max.): 4-5.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 3-13, 6-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size)

13=1508/0-5-8 (min. 0-2-0), 9=1508/0-5-8 (min. 0-2-0)

Max Horz 13=-221(LC 12)

Max Uplift 13=-2(LC 14), 9=-2(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-14=-678/92, 3-14=-537/116, 3-15=-241/10, 4-15=-2265/11, 4-16=-2436/0, 16-17=-2436/0, 17-18=-2436/0, 18-19=-2436/0, 5-19=-2436/0, 5-20=-2265/0, 6-20=-2411/0, 6-21=-527/119, 7-21=-678/94, 2-13=-669/133, 7-9=-669/135

BOT CHORD 12-13=-18/1979, 11-12=0/1787, 10-11=0/1787, 9-10=0/1979
WEBS 4-12=-8/358, 4-11=0/1166, 5-11=0/1166, 5-10=-10/358, 3-13=-2100/0, 6-9=-2100/0

NOTES- (12)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=28ft; eave=4ft; Cat. II; Exp B;

Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-2-0, Exterior(2) 10-2-0 to 14-4-15, Interior(1) 14-4-15 to 18-2-0, Exterior(2) 18-2-0 to 22-4-15, Interior(1) 22-4-15 to 29-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.

5) Provide adequate drainage to prevent water ponding.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

8) Bearing at joint(s) 13, 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 13, 9.

10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

12) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss S10G	Truss Type GABLE	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional)

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:33:13 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlyt-2?r1xIIIUs?WmNg3EkSt8fJxFJqU88QDlWkd3hz46fa

-0-10-8 5-2-12 10-2-0 4-11-4 18-2-0 8-0-0 23-1-4 4-11-4 28-4-0 5-2-12 29-2-8
0-10-8 5-2-12 4-11-4 8-0-0 4-11-4 5-2-12 0-10-8

Scale = 1:67.4




Plate Offsets (X,Y)-- [2:0-3-0,0-1-4], [3:0-1-12,0-1-12], [4:0-3-9,0-2-8], [5:0-3-9,0-2-8], [6:0-1-12,0-1-12], [7:0-3-0,0-1-4], [9:0-2-12,Edge], [11:0-3-0,0-0-2], [11:0-3-0,0-2-12], [13:0-2-12,Edge], [18:0-1-9,0-1-0], [21:0-1-9,0-1-0], [33:0-1-9,0-1-0], [36:0-1-9,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.72	Vert(LL) -0.28 in (loc) 9-10 >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.84	Vert(CT) -0.58 in (loc) 9-10 >578 180		
TCDL 10.0	Lumber DOL 1.15	WB 0.63	Horz(CT) 0.37 in (loc) 9 n/a n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S			
BCDL 10.0	Code IRC2015/TPI2014			Weight: 182 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
T2: 2x6 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E 3-11-10, Right 2x8 SP 2400F 2.0E 3-11-10

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-4-5 max.): 4-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-13, 6-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 13=1508/0-5-8 (min. 0-2-0), 9=1508/0-5-8 (min. 0-2-0)
Max Horz 13=-223(LC 12)
Max Uplift 13=-2(LC 14), 9=-2(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-41=-566/88, 3-41=-442/113, 3-42=-2386/0, 4-42=-2241/18, 4-43=-2383/0,
43-44=-2383/0, 44-45=-2383/0, 45-46=-2383/0, 5-46=-2383/0, 5-47=-2241/0,
6-47=-2386/0, 6-48=-428/115, 7-48=-566/90, 2-13=-591/130, 7-9=-591/132

BOT CHORD 12-13=-23/1930, 11-12=0/1767, 10-11=0/1767, 9-10=0/1930
WEBS 4-12=-12/353, 4-11=0/1129, 5-11=0/1129, 5-10=-14/353, 3-13=-2169/0, 6-9=-2169/0

NOTES- (15)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=28ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-2-0, Exterior(2) 10-2-0 to 14-4-15, Interior(1) 14-4-15 to 18-2-0, Exterior(2) 18-2-0 to 22-4-15, Interior(1) 22-4-15 to 29-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 6) Provide adequate drainage to prevent water ponding.
- 7) All plates are 2x4 MT20 unless otherwise indicated.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 11) Bearing at joint(s) 13, 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 13, 9.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	S10G	GABLE	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:33:13 2021 Page 2
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-2?f1xIIIUs?WmNg3EkSt8fJxFJqU88QDIWkd3hz46fa

NOTES- (15)

13) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

15) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss S11	Truss Type SCISSORS	Qty 8	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:34:12 2021 Page 1 ID:k67-5nKOKmB2GQsoap?Ao4zlytl-pLjLKT?Jb?R9LSgPBd0i15F8H51PSjuvsCWfemz46ef

-0-10-8 4-7-12 9-0-0 4-4-4 13-4-4 18-0-0 18-10-8
0-10-8 4-7-12 4-4-4 4-4-4 4-7-12 0-10-8

4x4 =

Scale = 1:60.8




Plate Offsets (X,Y)-- [2:0-2-0,0-1-4], [3:0-1-12,0-2-0], [5:0-1-12,0-2-0], [6:0-2-0,0-1-4], [9:0-4-0,0-3-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.27	Vert(LL) -0.21	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.64	Vert(CT) -0.43		
TCDL 10.0	Rep Stress Incr YES	WB 0.96	Horz(CT) 0.14		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 88 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E 3-6-11, Right 2x8 SP 2400F 2.0E 3-6-11

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-1-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 10=983/0-3-8 (min. 0-1-8), 8=983/0-3-8 (min. 0-1-8)
Max Horz 10=198(LC 13)
Max Uplift 10=10(LC 14), 8=10(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-11=-411/67, 3-11=-312/87, 3-12=-1215/0, 4-12=-1077/0, 4-13=-1077/0, 5-13=-1215/0,
5-14=-305/89, 6-14=-409/69, 2-10=-462/111, 6-8=-462/112

BOT CHORD 9-10=-27/1129, 8-9=0/1084
WEBS 4-9=0/1174, 3-10=-1161/0, 5-8=-1161/0

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 9-0-0, Exterior(2) 9-0-0 to 12-0-0, Interior(1) 12-0-0 to 18-10-8 zone: cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 10, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 8.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss S12	Truss Type SCISSORS	Qty 2	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:36:40 2021 Page 1 ID:k67_5nOKmB2GQsoap?Ao4zlytl-UqflO4o8kT495B_rsigP1JNTjlfR8sOhuDN4qBz46cl

0-10-8 2-5-6 4-7-4 6-9-2 9-2-0
0-10-8 2-5-6 2-1-14 2-1-14 2-4-14

4x4 =

Scale = 1:38.2




Plate Offsets (X,Y)-- [8:0-4-0,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.10	Vert(LL) -0.02	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.16	Vert(CT) -0.03		
TCDL 10.0	Rep Stress Incr YES	WB 0.14	Horz(CT) 0.02		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	(loc) 8-9 >999		
BCDL 10.0			l/defl 7 n/a		
			L/d 240 n/a		
				Weight: 47 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x8 SP 2400F 2.0E 2-2-9

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=539/0-3-8 (min. 0-1-8), 7=446/0-5-8 (min. 0-1-8)
Max Horz 9=114(LC 13)
Max Uplift 9=16(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-4=-517/62, 4-11=-453/69, 5-11=-519/51
BOT CHORD 8-9=-58/431, 7-8=-50/410
WEBS 4-8=-44/449, 3-9=-529/6, 5-7=-530/51

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-3-9, Interior(1) 2-3-9 to 4-7-4, Exterior(2) 4-7-4 to 7-7-4, Interior(1) 7-7-4 to 9-0-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 9, 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) CUSTOMER SIGNATURE: _____


LOAD CASE(S) Standard

Job Q104-179RT	Truss S12G	Truss Type GABLE	Qty 2	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:37:17 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-vxPH9kEL1rv1tJyXzq516PoNgH5JbY7PUrXdYz46bm

0-10-8 2-5-6 4-7-4 6-9-2 9-2-0
0-10-8 2-5-6 2-1-14 2-1-14 2-4-14

4x4 =

Scale = 1:38.2



0-0-8 4-7-4 8-8-8 9-2-0
0-0-8 4-6-12 4-1-4 0-5-8

Plate Offsets (X,Y)-- [3:0-4-0,0-3-0], [5:0-4-0,0-3-0], [8:0-4-0,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.10	Vert(LL) -0.02	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.16	Vert(CT) -0.03		
TCDL 10.0	Rep Stress Incr YES	WB 0.14	Horz(CT) 0.02		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	(loc) 8-9 >999		
BCDL 10.0			l/defl 7 n/a		
			L/d 240 n/a		
			Weight: 50 lb FT = 10%		

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=539/0-3-8 (min. 0-1-8), 7=446/0-5-8 (min. 0-1-8)
Max Horz 9=114(LC 13)
Max Uplift 9=16(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-4=-517/62, 4-13=-453/69, 5-13=-519/51
BOT CHORD 8-9=-58/431, 7-8=-50/410
WEBS 4-8=-44/449, 3-9=-529/6, 5-7=-530/51

NOTES- (12)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-3-9, Interior(1) 2-3-9 to 4-7-4, Exterior(2) 4-7-4 to 7-7-4, Interior(1) 7-7-4 to 9-0-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 9) Bearing at joint(s) 9, 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T01	Truss Type Attic	Qty 13	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:38:48 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-kSOhFrLrb0C_SsnRMazRDIhA9EMem7iGXK8NrKmz46aL

-0-10-8 6-10-4 9-6-14 10-4-13 13-0-0 17-0-0 19-7-3 20-5-2 23-1-12 30-0-0 30-10-8
0-10-8 6-10-4 2-8-10 0-9-15 2-7-3 4-0-0 2-7-3 0-9-15 2-8-10 6-10-4 0-10-8

Scale = 1:69.9




Plate Offsets (X,Y)-- [2:Edge,0-0-5], [3:0-4-11,0-1-0], [4:0-0-14,0-0-0], [5:0-6-0,Edge], [6:0-5-4,0-2-12], [7:0-3-0,0-2-12], [8:0-6-0,Edge], [9:0-0-14,0-0-0], [10:0-4-11,0-1-0], [11:0-2-1,0-2-0], [13:0-6-0,0-1-8], [15:0-6-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.82	Vert(LL) -0.71 13-15	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.52	Vert(CT) -0.97 13-15	MT18HS	244/190
TCDL 10.0	Rep Stress Incr YES	WB 0.38	Horz(CT) 0.02 11		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	Attic -0.38 13-15	516	360
BCDL 10.0				Weight: 245 lb	FT = 10%

LUMBER-	BRACING-	
TOP CHORD 2x6 SP 2400F 1.8E *Except* T3: 2x6 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 4-0-3 oc purlins, except 2-0-0 oc purlins (6-0-0 max.); 6-7.
BOT CHORD 2x10 SP 2400F 2.0E	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SPF No.2	JOINTS	1 Brace at Jt(s): 16, 17
WEDGE		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.
Left: 2x4 SPF No.2 , Right: 2x4 SPF No.2		

REACTIONS. (lb/size) 2=1672/0-5-8 (min. 0-1-11), 11=1672/0-5-8 (min. 0-1-11)
Max Horz 2=200(LC 13)
Max Grav 2=2018(LC 21), 11=2018(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-18=-2694/0, 3-18=-2428/0, 3-19=-1702/68, 4-19=-1560/102, 4-5=-343/290,
5-6=-305/320, 6-7=-125/513, 7-8=-299/330, 8-9=-337/300, 9-20=-1560/102,
10-20=-1702/68, 10-21=-2428/0, 11-21=-2693/0

BOT CHORD 2-22=0/1744, 15-22=0/1744, 14-15=0/1744, 13-14=0/1744, 13-23=0/1744, 11-23=0/1744
WEBS 3-15=0/1215, 4-17=2018/81, 16-17=2014/82, 9-16=2031/82, 10-13=0/1214

NOTES- (14)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 13-0-0, Exterior(2) 13-0-0 to 21-2-15, Interior(1) 21-2-15 to 30-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Ceiling dead load (5.0 psf) on member(s). 3-4, 9-10, 4-17, 16-17, 9-16
- 10) Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 13-15
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) Attic room checked for L/360 deflection.
- 14) CUSTOMER SIGNATURE:

Continued on page 2

Job Q104-179RT	Truss T01	Truss Type Attic	Qty 13	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	---------------------	-----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8,420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:38:48 2021 Page 2
ID:k67_5nOKmB2GQsoap?Ao4zlytl-kSOhFrLboC_SsnRMazRDIhA9MEm7iGXK8NrKmz46aL

LOAD CASE(S) Standard

Job Q104-179RT	Truss T02	Truss Type Attic	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:39:58 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-hwd8xnBL6l13rd7uTHDr33a6rZ7KXLxqQ1LYnjz46ZF

-0-10-8 6-10-4 9-6-14 10-4-13 13-0-0 17-0-0 19-7-3 20-5-2 23-1-12 30-0-0 30-10-8
0-10-8 6-10-4 2-8-10 0-9-15 2-7-3 4-0-0 2-7-3 0-9-15 2-8-10 6-10-4 0-10-8

Scale = 1:73.4




Plate Offsets (X,Y)-- [2:0-1-10,0-1-12], [3:0-2-8,0-3-12], [5:0-6-0,Edge], [6:0-5-4,0-2-12], [7:0-3-0,0-2-12], [8:0-7-0,Edge], [10:0-0-1,0-1-4], [11:0-2-1,0-2-4], [13:0-5-8,0-1-8], [15:0-6-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.92	Vert(LL) -0.65 13-15	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.51	Vert(CT) -0.89 13-15	MT18HS	197/144
TCDL 10.0	Rep Stress Incr YES	WB 0.42	Horz(CT) 0.02 11		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	Attic -0.37 13-15	Weight: 251 lb	FT = 10%
BCDL 10.0					

LUMBER-

TOP CHORD 2x6 SPF No.2 *Except*
T1,T5: 2x6 SP 2400F 1.8E
BOT CHORD 2x10 SP 2400F 2.0E
WEBS 2x4 SPF No.2
WEDGE
Left: 2x6 SPF No.2 , Right: 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 6-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-16
JOINTS 1 Brace at Jt(s): 17, 18

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 16=1750/0-7-12 (min. 0-1-11), 11=1599/0-5-8 (min. 0-1-9)

Max Horz 16=-200(LC 12)

Max Grav 16=2037(LC 21), 11=1922(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-19=-990/0, 3-19=-720/35, 3-20=-1566/66, 4-20=-1425/99, 4-5=-399/224,
5-6=-361/254, 6-7=-181/409, 7-8=-343/259, 8-9=-381/229, 9-21=-1403/101,

10-21=-1545/68, 10-22=-2148/0, 11-22=-2414/0

BOT CHORD 2-16=0/472, 15-16=0/1551, 14-15=0/1551, 13-14=0/1551, 13-23=0/1551, 11-23=0/1551
WEBS 3-15=0/1186, 4-17=-1734/76, 17-18=-1730/77, 9-18=-1706/81, 10-13=-1/1067,
3-16=-1626/0

NOTES- (14)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 13-0-0, Exterior(2) 13-0-0 to 21-2-15, Interior(1) 21-2-15 to 30-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Ceiling dead load (5.0 psf) on member(s). 3-4, 9-10, 4-17, 17-18, 9-18
- 10) Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 13-15
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T02	Attic	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:39:58 2021 Page 2

ID:k67_5nOKmB2GQsoap?Ao4zlytl-hwd8xnBL6l13rd7uTHDr33a6rZ7KXLxqQ1LYnjz46ZF

NOTES- (14)

13) Attic room checked for L/360 deflection.

14) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T03	Truss Type Attic	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:41:05 2021 Page 1

-0-10-8 6-10-4 9-6-14 10-4-13 13-0-0 17-0-0 19-7-3 20-5-2 23-1-12 30-0-0 30-10-8
0-10-8 6-10-4 2-8-10 0-9-15 2-7-3 4-0-0 2-7-3 0-9-15 2-8-10 6-10-4 0-10-8




Plate Offsets (X,Y)-- [2:0-2-1,0-2-8], [3:0-1-4,0-1-8], [5:0-7-0,Edge], [6:0-5-4,0-2-12], [7:0-3-0,0-2-12], [11:0-8-0,0-0-3], [13:0-4-12,0-1-8], [15:0-7-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.79	Vert(LL) -0.58 13-15 >541 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.50	Vert(CT) -0.79 13-15 >399 180	MT20HS	148/108
TCDL 10.0	Rep Stress Incr YES	WB 0.55	Horz(CT) 0.01 11 n/a n/a	MT18HS	244/190
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	Attic -0.36 13-15 546 360	Weight: 248 lb	FT = 10%

LUMBER-

TOP CHORD 2x6 SPF No.2 *Except*
T1,T5: 2x6 SP 2400F 1.8E

BOT CHORD 2x10 SP 2400F 2.0E

WEBS 2x4 SPF No.2

WEDGE

Left: 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-8-12 oc purlins, except
2-0-0 oc purlins (6-0-0 max.): 6-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 2-16.
WEBS 1 Row at midpt 3-16
JOINTS 1 Brace at Jt(s): 17, 18

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 16=1885/0-7-12 (min. 0-1-13), 11=1464/0-5-8 (min. 0-1-8)

Max Horz 16=200(LC 13)

Max Uplift 16=1(LC 14)

Max Grav 16=2179(LC 24), 11=1767(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-19=-92/362, 3-20=-1369/57, 4-20=-1227/90, 4-5=-487/146, 5-6=-448/177,
6-7=-286/287, 7-8=-447/176, 8-9=-486/145, 9-21=-1176/95, 10-21=-1318/61,
10-22=-1735/0, 11-22=-2001/0

BOT CHORD 15-16=0/1272, 14-15=0/1272, 13-14=0/1272, 13-23=0/1272, 11-23=0/1272
WEBS 3-15=0/1656, 4-17=-1330/57, 17-18=-1327/58, 9-18=-1271/68, 10-13=-145/866,
3-16=-2782/16

NOTES- (15)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=30ft; eave=4ft; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2) 0-10-8 to 2-1-8, Interior(1) 2-1-8 to 13-0-0, Exterior(2) 13-0-0 to 21-2-15,
Interior(1) 21-2-15 to 30-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces
& MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat
roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs
non-concurrent with other live loads.

5) Provide adequate drainage to prevent water ponding.

6) All plates are MT20 plates unless otherwise indicated.

7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide
will fit between the bottom chord and any other members, with BCDL = 10.0psf.

9) Ceiling dead load (5.0 psf) on member(s). 3-4, 9-10, 4-17, 17-18, 9-18

10) Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 13-15

11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T03	Attic	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:41:05 2021 Page 2
ID:k67_5nKOKmB2GQsoap?Ao4zlyl-EpAT?h?MKuTYOwlhuswZHBsb4a0Akdyhqv3beKz46YC

NOTES- (15)

12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

14) Attic room checked for L/360 deflection.

15) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T04	Truss Type Piggyback Base	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:46:58 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-Oj?w5OGoCLxTEAEd3UmL4dzz_tVPxGLf?N4nWNz46Sh

3-7-7 6-11-6 10-11-6 17-3-10 23-11-6 24-9-14
3-7-7 3-3-15 4-0-0 6-4-4 6-7-12 0-10-8

Scale = 1:71.7




Plate Offsets (X,Y)-- [1:0-3-0,Edge], [3:0-4-4,0-2-0], [4:0-4-4,0-2-0], [6:0-1-8,0-1-8], [8:0-7-7,Edge], [14:0-1-8,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.59	Vert(LL) -0.07 13-14 >999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.46	Vert(CT) -0.13 13-14 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.52	Horz(CT) 0.03 8 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 165 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2
SLIDER Right 2x8 SP 2400F 2.0E 4-5-5

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-9-2 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 4-13, 6-12, 2-14

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=1286/0-5-8 (min. 0-2-0), 16=1174/0-1-8 (min. 0-1-8)
Max Horz 16=-157(LC 10)
Max Grav 8=1286(LC 1), 16=1192(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-775/158, 3-4=-528/141, 4-5=-850/140, 5-18=-861/115, 6-18=-1016/96,
6-7=-1340/49, 7-19=-1419/17, 8-19=-1490/12, 14-15=0/1021, 1-15=0/1021
BOT CHORD 14-20=0/500, 20-21=0/500, 13-21=0/500, 13-22=0/687, 12-22=0/687, 12-23=0/1010,
11-23=0/1010, 10-11=0/1010, 10-24=0/1010, 8-24=0/1010
WEBS 2-13=0/370, 4-13=-406/40, 4-12=-21/547, 6-12=-575/114, 6-10=0/322, 2-14=-984/34,
1-16=-1195/56

NOTES- (12)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-6-13, Interior(1) 3-6-13 to 6-11-6, Exterior(2) 6-11-6 to 15-2-4, Interior(1) 15-2-4 to 24-9-14 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Bearing at joint(s) 16 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 16.
- 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 12) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job	Truss	10.00	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T05		Piggyback Base	1	1	
Job Reference (optional)						8420 S. Dec 30, 2020 MiTek Industries, Inc. Mon, Jun 21 09:48:52 2021 Page 1



LUMBER-
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2
SLIDER Right 2x8 SP 2400F 2.0E 4-5-5

REACTIONS. (lb/size) 8=1184/0-5-8 (min. 0-1-14), 15=1072/0-1-8 (min. 0-1-8)
Max Horz 15=-177(LC 14)
Max Uplift 15=-10(LC 14).

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-16=-533/124, 3-16=-479/136, 3-4=-366/119, 4-5=-693/118, 5-17=-704/94, 6-17=-868/74, 6-7=-1097/29, 7-18=-1262/0, 8-18=-1333/0, 1-14=-33/926
BOT CHORD	13-14=-26/343, 13-19=0/563, 12-19=0/563, 12-20=0/893, 11-20=0/893, 10-11=0/893, 10-21=0/893, 8-21=0/893
WEBS	2-13=-4/500, 4-13=-536/53, 4-12=-19/580, 6-12=-584/116, 6-10=0/318, 2-14=-884/82, 1-15=-1074/70

NOTES- (13)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-5-4, Interior(1) 3-5-4 to 4-11-6, Exterior(2) 4-11-6 to 13-2-4, Interior(1) 13-2-4 to 22-9-14 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Bearing at joint(s) 15 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 15.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 15.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) CUSTOMER SIGNATURE: _____
Continued on page 2.

13) CUSTOMER SIGNATURE: _____
Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T05	Piggyback Base	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:48:52 2021 Page 2
ID:k67_5nOKmB2GQsoap?Ao4zlytl-2fu00NflMNJHvhyXIRo4igiS0qQWetoQD6hpWmz46Qv

LOAD CASE(S) Standard

Job Q104-179RT	Truss T06	Truss Type Piggyback Base	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:49:21 2021 Page 1 ID:k67_5nKOKmB2GQsop?Ao4zlyt-iE8_6!UXHzAu8g6x1qtNnOQgWPxyoiu7Dr2az46QS

2-11-6 6-11-6 4-0-0 13-3-10 6-4-4 19-11-6 6-7-12 20-9-14 0-10-8

Scale = 1:77.1




Plate Offsets (X,Y)-- [1:0-3-0,Edge], [2:0-6-4,0-2-0], [3:0-3-4,0-2-0], [5:0-1-8,0-1-8], [7:0-7-7,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.54	Vert(LL)	-0.04	7-9	>999	240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.43	Vert(CT)	-0.09	7-9	>999	180		
TCDL 10.0	Rep Stress Incr YES	WB 0.52	Horz(CT)	0.02	7	n/a	n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S						Weight: 155 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2
SLIDER Right 2x8 SP 2400F 2.0E 4-5-5

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-8-1 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 2-3.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 2-12, 3-11, 5-11, 2-13, 1-14

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=1083/0-5-8 (min. 0-1-11), 14=971/0-1-8 (min. 0-1-8)

Max Horz 14=-215(LC 14)

Max Uplift 14=-29(LC 14)

Max Grav 7=1083(LC 1), 14=974(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-417/111, 3-4=-527/82, 4-15=-543/58, 5-15=-707/38, 5-6=-951/0, 6-16=-1116/0, 7-16=-1187/0, 1-13=-41/866

BOT CHORD 12-13=-88/292, 12-17=-79/280, 11-17=-79/280, 11-18=0/784, 10-18=0/784, 9-10=0/784, 9-19=0/784, 7-19=0/784

WEBS 2-11=-70/620, 5-11=-602/118, 5-9=0/328, 2-13=-832/105, 1-14=-975/90

NOTES- (13)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 11-2-4, Interior(1) 11-2-4 to 20-9-14 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 14.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) CUSTOMER SIGNATURE:

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T06	Piggyback Base	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:49:21 2021 Page 2
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-iE8_6I?UXHzAu8g6x1qtNnOQgWJPxyoiu7Dr2az46QS

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T07	Piggyback Base	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:50:34 2021 Page 2
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-3G3aQFuHKj9p9MI7jse_rBwuHyEwYviRg_PD6rz46PJ

LOAD CASE(S) Standard

Job Q104-179RT	Truss T08	Truss Type Common	Qty 1	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:50:56 2021 Page 1

ID:k67_5nOKmB2GQsoap?Ao4zlytl-QVOu2n949TxholRM0T19kpqbcpiPiuxhkPkNtaz46Oz
0-11-6 8-3-10 15-11-6 16-9-14
0-11-6 7-4-4 7-7-12 0-10-8




Plate Offsets (X,Y)-- [1:0-3-0,Edge], [2:0-2-8,0-1-12], [6:0-5-15,0-0-1], [8:0-1-12,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.81	Vert(LL) -0.22	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.57	Vert(CT) -0.32		
TCDL 10.0	Rep Stress Incr YES	WB 0.61	Horz(CT) 0.04		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 126 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2
SLIDER Right 2x8 SP 2400F 2.0E 5-1-2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-9-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 2-8, 2-10
2 Rows at 1/3 pts 1-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=880/0-5-8 (min. 0-1-8), 11=767/Mechanical

Max Horz 11=-279(LC 14)

Max Uplift 11=-93(LC 14)

Max Grav 6=880(LC 1), 11=852(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-12=-701/17, 3-12=-710/93, 3-4=-907/66, 4-5=-690/0, 5-13=-755/0, 6-13=-861/0,
1-10=-153/879

BOT CHORD 9-14=-249/297, 14-15=-249/297, 8-15=-249/297, 6-8=0/530
WEBS 2-8=-211/1014, 4-8=-657/269, 2-10=-776/206, 1-11=-852/133

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-11-6, Interior(1) 3-11-6 to 16-9-14 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T09	Truss Type COMMON	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:57:53 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-jk4YZMCFybTXJqpVxY0x7lcUv2AvT03dnFx0vz46IS

15-7-6

2-7-0

0-3-8

6-7-15

13-0-6

6-4-7

15-10-14

14-7-6

Scale = 1:82.0




Plate Offsets (X,Y)-- [3:0-1-8,0-1-8], [4:0-3-12,0-1-8], [6:0-1-8,0-2-0], [9:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.61	Vert(LL) -0.08	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.49	Vert(CT) -0.16		
TCDL 10.0	Rep Stress Incr YES	WB 0.75	Horz(CT) 0.12		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 101 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-9-2 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-9, 1-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=797/0-5-8 (min. 0-1-8), 11=760/Mechanical

Max Horz 11=-300(LC 14)

Max Uplift 11=-77(LC 14)

Max Grav 6=797(LC 1), 11=773(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 9-10=-35/602, 1-10=-35/602, 3-4=-813/0

BOT CHORD 9-12=0/517, 8-12=0/517, 7-8=0/1291, 6-7=0/1796

WEBS 3-9=-736/110, 3-8=0/404, 4-8=-798/67, 4-7=0/1178, 4-6=-2169/0, 1-11=-774/114

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-5-4, Interior(1) 3-5-4 to 15-9-2 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T10	Truss Type Common	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:57:18 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-E?TJDOnhBr3VdSenOitkDNfzCo6ECeZvZqGbIRz46J?

5-7-15 11-0-6 13-7-6
5-7-15 5-4-7 2-6-15 0-3-8
13-10-14

Scale = 1:72.7




Plate Offsets (X,Y)-- [1:0-3-0,Edge], [3:0-1-8,0-1-8], [4:0-2-12,0-1-8], [6:0-1-8,0-2-0], [9:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.42	Vert(LL) -0.06	7-8	>999	240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.41	Vert(CT) -0.11	7-8	>999	180		
TCDL 10.0	Rep Stress Incr YES	WB 0.67	Horz(CT) 0.09	6	n/a	n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S					Weight: 88 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 1-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=695/0-5-8 (min. 0-1-8), 11=658/0-1-8 (min. 0-1-8)

Max Horz 11=-263(LC 14)

Max Uplift 11=-62(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 9-10=-34/507, 1-10=-34/507, 3-4=-691/0

BOT CHORD 8-9=0/441, 7-8=0/1069, 6-7=0/1488

WEBS 3-9=-618/101, 3-8=0/353, 4-8=-655/64, 4-7=0/979, 4-6=-1781/0, 1-11=-659/99

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-5-4, Interior(1) 3-5-4 to 13-9-2 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 6, 11 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 11.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T11	Truss Type Common	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:05 2021 Page 1

ID:k67_5nOKmB2GQsoa
3.3 11 12 14

17/17 ID:k67_5nOKmB2GQssoap?A04zlytl-kdnsuZhZPwfZfJs2pPxpRkxocJK41KqGluEnVyz4/6m

Scale = 1:57.1




Plate Offsets (X,Y)-- [3:0-1-12,0-1-8], [6:0-3-14,Edge], [7:0-3-0,0-2-12], [8:0-1-8,0-2-0]

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEB 2x4 SPF No.2

BRACING-

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 5-3-11 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBBS	1 Row at midpt 1-8

REACTIONS. (lb/size) 8=564/Mechanical, 6=967/0-5-8 (min. 0-1-8), 5=-351/0-5-8 (min. 0-1-8)
Max Horz 8=271(LC 10)
Max Vert 8=45 (LC 10), 271 (LC 11)

FORCES (lb) - Max. Comp./Max. Tens. - All forces 250 (lb) or less except when shown.

FORCES. (lb) - Max. Comp./Max.

TOP CHORD 2-3=-1100/169
BOT CHORD 3 8 113/252 6 3 10/1053

BOT CHORD 7-8=-11/7352, 6-7=-10/1057
WERS 3.8- 445/126, 3.7- 91/717, 3.7- 82/236, 3.6- 1423/2

NOTES. (8)

NOTES- (8)

- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 11-9-2 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8 except (jt=lb) 5=351.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss T12	Truss Type Common	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:59:13 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-N7wnLjAq6AYAw7wtdMRiNdwZc9M_eg9q0DdAqGz46HC 7-0-6 7-0-6 2-6-15 0-3-8

Scale = 1:59.3




Plate Offsets (X,Y)-- [1:0-3-4,0-1-0], [2:0-2-8,0-1-8], [4:0-2-8,0-1-8], [5:0-1-12,0-2-0], [6:0-1-12,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.59	Vert(LL)	-0.08	5-6	>999	240	
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.42	Vert(CT)	-0.17	5-6	>701	180	
TCDL 10.0	Rep Stress Incr YES	WB 0.60	Horz(CT)	0.07	4	n/a	n/a	
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S					Weight: 56 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=492/0-5-8 (min. 0-1-8), 8=455/0-1-8 (min. 0-1-8)
Max Horz 8=188(LC 14)
Max Uplift 8=32(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 6-7=0/252, 1-7=0/252
BOT CHORD 5-6=0/807, 4-5=0/1140
WEBS 2-6=-777/146, 2-5=0/787, 2-4=-1391/0, 1-8=-457/69

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-5-4, Interior(1) 3-5-4 to 9-9-2 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 4, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 8.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T13	Truss Type Common	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:00:28 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-gYy85M4tRD?XPe9IWclHvRWUMO_qjf2tGOleyQz46G1

5-0-6 7-7-6 7-10-14
5-0-6 2-6-15 0-3-8

Scale = 1:48.6




Plate Offsets (X,Y)-- [1:0-3-0,0-1-4], [2:0-2-8,0-1-8], [4:0-2-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.22	Vert(LL) -0.03 in (loc) 5-6 >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.27	Vert(CT) -0.07 5-6 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.32	Horz(CT) 0.05 4 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 45 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=390/0-5-8 (min. 0-1-8), 8=354/0-1-8 (min. 0-1-8)
Max Horz 8=150(LC 14)
Max Uplift 8=17(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

BOT CHORD 5-6=0/521, 4-5=0/745
WEBS 2-6=504/96, 2-5=0/535, 2-4=-933/0, 1-8=-356/54

NOTES- (9)

- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-5-4 to 3-5-4, Interior(1) 3-5-4 to 7-9-2 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 4, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 8.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T14	Truss Type Common	Qty 1	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:01:11 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-wq2O63br.JRPR4FyZX8ZN9WoqhjVI9cC8aCQzQz46FM
4-5-10 4-9-2
4-5-10 0-3-8

Scale = 1:24.4




Plate Offsets (X,Y)-- [1:0-3-0,Edge], [2:0-1-13,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.21	Vert(LL) -0.01 in (loc) 2-3 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.17	Vert(CT) -0.02 in (loc) 2-3 l/defl >999 L/d 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.13	Horz(CT) -0.00 in (loc) 2 n/a L/d n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-R			
BCDL 10.0				Weight: 20 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-9-2 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=225/0-7-0 (min. 0-1-8), 5=190/0-1-8 (min. 0-1-8)
Max Horz 5=70(LC 14)
Max Uplift5=19(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____


LOAD CASE(S) Standard

Job Q104-179RT	Truss T15	Truss Type Piggyback Base	Qty 9	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional)

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:01:59 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-W3yXBUAy0BTdqqdnLDQd5do_742lYscGB2qzezez46Ec

-0-10-8 5-6-14 10-10-4 14-10-4 20-1-6 25-4-8 25-8-0
0-10-8 5-6-14 5-3-6 4-0-0 5-3-2 5-3-2 0-3-8

Scale = 1:70.4



0-0-8 5-6-14 10-10-4 14-10-4 20-1-6 25-4-8 25-8-0
0-0-8 5-6-6 5-3-6 4-0-0 5-3-2 5-3-2 0-3-8

Plate Offsets (X,Y)-- [2:0-3-8,Edge], [3:0-1-4,0-2-0], [5:0-6-4,0-1-12], [6:0-3-4,0-1-12], [7:0-1-4,0-2-0], [8:0-0-12,0-1-8], [9:0-2-0,0-1-0], [15:0-2-0,0-0-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.43	Vert(LL) -0.04 in (loc) 13 l/defl >999 L/d 240	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.30	Vert(CT) -0.08 13-14 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.19	Horz(CT) 0.02 9 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 155 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-4-3 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-13, 5-12, 7-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 15=1374/0-5-8 (min. 0-2-2), 9=1287/0-5-4 (min. 0-2-0)
Max Horz 15=222(LC 13)
Max Uplift 15=4(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-16=-1454/51, 3-16=-1172/80, 3-17=-1158/133, 4-17=-1046/145, 4-5=-989/173,
5-18=-701/168, 18-19=-701/168, 6-19=-701/168, 6-20=-988/178, 7-20=-1160/137,
7-21=-1269/80, 8-21=-1442/54, 2-15=-1322/95, 8-9=-1235/66

BOT CHORD 14-15=-164/360, 13-14=0/947, 13-22=0/718, 12-22=0/718, 11-12=0/923, 10-11=0/923
WEBS 3-13=-355/123, 5-13=-40/405, 6-12=-53/373, 7-12=-358/125, 2-14=0/718, 8-10=0/771

NOTES- (11)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=26ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-10-4, Exterior(2) 10-10-4 to 19-1-3, Interior(1) 19-1-3 to 25-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 15.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 11) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss T16	Truss Type Piggyback Base	Qty 8	Ply 1	BANDY RESIDENCE Job Reference (optional)
-------------------	--------------	------------------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:02:47 2021 Page 1

| 5-3-14 | 10-4-4 | 14-4-4 | 19-7-6 | 24-10-8 | 25-2-0 |

| 5-3-14 | 5-0-6 | 4-0-0 | 5-3-2 | 5-3-2 | 0-3-8 |

Scale = 1:70.4




Plate Offsets (X,Y)- [1:0-1-0,0-1-8], [2:0-1-4,0-2-0], [3:0-6-4,0-1-12], [4:0-3-4,0-1-12], [5:0-1-4,0-2-0], [6:0-0-12,0-1-8], [12:0-1-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof) Snow (Pf/Pg)	30.0 30.8/40.0	Plate Grip DOL Lumber DOL	1.15 1.15	TC BC	0.43 0.29	Vert(LL) Vert(CT)	-0.03 10-11 -0.07 11-12	>999 >999	240 180
TCDL	10.0	Rep Stress Incr	YES	WB	0.19	Horz(CT)	0.02 7	n/a	n/a
BCLL	0.0 *	Code IRC2015/TPI2014		Matrix-S					
BCDL	10.0							Weight: 153 lb	FT = 10%

LUMBER-

LUMBER-
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WFBS 2x4 SPF No.2

BRACING-

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 4-4-13 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBBS	1 Row at midpt 2-11, 3-10, 5-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer installation guide.

REACTIONS. (lb/size) 13=1264/Mechanical, 7=1264/0-5-8 (min. 0-2-0)
Max Horz 13=-214(LC 12)

FORCES. (lb) -

STREETS (1)	MAX: 1321/55, 2-14=-1052/80, 2-15=-1109/140, 3-15=-944/178, 3-16=-679/169, 4-16=-679/169, 4-17=-957/177, 5-17=-1129/137, 5-18=-1240/80, 6-18=-1413/53, 1-13=-1214/65, 6-7=-1211/66
TOP CHORD	1-14=-1321/55, 2-14=-1052/80, 2-15=-1109/140, 3-15=-944/178, 3-16=-679/169, 4-16=-679/169, 4-17=-957/177, 5-17=-1129/137, 5-18=-1240/80, 6-18=-1413/53, 1-13=-1214/65, 6-7=-1211/66
BOT CHORD	11-12=-0/873, 11-19=0/690, 10-19=0/690, 9-10=0/902, 8-9=0/902
WEBS	2-11=-299/123, 3-11=-46/368, 4-10=-51/350, 5-10=-359/124, 1-12=0/776, 6-8=0/751

NOTES- (10)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=25ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 10-4-4, Exterior(2) 10-4-4 to 18-7-3, Interior(1) 18-7-3 to 25-0-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

4) Provide adequate drainage to prevent water ponding.

5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

7) Refer to girder(s) for truss to truss connections.

8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

10) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T16G	Truss Type GABLE	Qty 2	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:03:47 2021 Page 1
ID:k67_5nOKmB2GQsoap?Ao4zlytl-LqTMsPUiaM3lnEtYgvMyUPGWDcyTrirA0s?gRoZ46Cw
-0-10-8 10-10-4 14-10-4 25-4-8 25-8-0
0-10-8 10-10-4 4-0-0 10-6-4 0-3-8

Scale = 1:70.3




Plate Offsets (X,Y)-- [9:0-2-4,0-1-12], [11:0-2-4,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.09	Vert(LL) 0.00 in (loc) 1 l/defl n/r L/d 120	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.08	Vert(CT) -0.00 1 n/r 120		
TCDL 10.0	Rep Stress Incr YES	WB 0.16	Horz(CT) -0.00 18 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-R			
BCDL 10.0				Weight: 171 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 9-11.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 8-28, 9-27, 10-26, 11-25, 12-23

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 25-8-0.
(lb) - Max Horz 33=222(LC 13)
Max Uplift All uplift 100 lb or less at joint(s) 31, 30, 29, 28, 23, 22, 21, 20 except 33=217(LC 12), 18=193(LC 13), 32=160(LC 11), 19=132(LC 10)
Max Grav All reactions 250 lb or less at joint(s) 18, 32, 31, 30, 29, 28, 27, 26, 25, 23, 22, 21, 20, 19 except 33=322(LC 21)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 8-9-=253/294, 11-12-=253/294

NOTES- (16)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=26ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3) -0-10-8 to 2-1-8, Exterior(2) 2-1-8 to 10-10-4, Corner(3) 10-10-4 to 13-10-4, Exterior(2) 13-10-4 to 14-10-4, Corner(3) 14-10-4 to 17-10-4, Exterior(2) 17-10-4 to 25-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 30.8 psf on overhangs non-concurrent with other live loads.
- 6) Provide adequate drainage to prevent water ponding.
- 7) All plates are 2x4 MT20 unless otherwise indicated.
- 8) Gable requires continuous bottom chord bearing.
- 9) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 10) Gable studs spaced at 2-0-0 oc.
- 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 12) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 31, 30, 29, 28, 23, 22, 21, 20 except (jt=lb) 33=217, 18=193, 32=160, 19=132.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T16G	GABLE	2	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:03:47 2021 Page 2
ID:k67_5nOKmB2GQsoap?Ao4zlytl-LqTMsPUiaM3InEtYgvMyUPGWDcyTrirA0s?gROz46Cw

NOTES- (16)

14) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

15) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


16) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T17	Truss Type Piggyback Base	Qty 6	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:05:35 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-Bc?BXLoR8Ygzlq7I?alHsBkte8jB9TW3sf9OE7z46BE

4-1-8 7-11-8 10-0-0 14-0-0 15-5-0 19-5-12 23-6-8 23-10-0
4-1-8 3-10-0 2-0-8 4-0-0 1-5-0 4-0-12 4-0-12 0-3-8

Scale: 3/16"=1"



0-0-8 4-1-8 7-11-8 10-0-0 14-0-0 15-10-8
0-0-8 4-1-0 3-10-0 2-0-8 4-0-0 1-5-0 5-8
6.00 12 12.00 12

Plate Offsets (X,Y)-- [1:0-0-15,Edge], [3:0-1-4,0-1-8], [4:0-1-4,0-1-8], [5:0-2-4,0-1-12], [6:0-6-4,0-1-12], [7:0-1-4,0-1-8], [10:0-5-11,0-0-1], [11:0-3-4,0-2-4], [14:0-2-8,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP	
TCLL (roof) Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL Lumber DOL	2-0-0 1.15 1.15	TC 0.49 BC 0.50 WB 0.48 Matrix-S	Vert(LL) -0.05 14-15 Vert(CT) -0.08 14-15 Horz(CT) 0.09 11	in (loc) l/defl L/d >999 >999 n/a	240 180 n/a
TCDL BCLL BCDL	Rep Stress Incr Code IRC2015/TPI2014					
				Weight: 152 lb	FT = 10%	

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
SLIDER Left 2x6 SPF No.2 3-0-12, Right 2x6 SPF No.2 3-2-11

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-0-15 oc purlins, except
2-0-0 oc purlins (6-0-0 max.): 5-6.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 6-12, 7-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=541/0-5-8 (min. 0-1-8), 11=1867/0-5-8 (min. 0-2-15)
Max Horz 1=187(LC 12)
Max Grav 1=668(LC 27), 11=1867(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-1177/0, 2-16=-1062/0, 3-16=-991/0, 3-17=-751/47, 4-17=-675/78, 4-5=-384/134,
6-7=-27/377, 7-20=-81/632, 8-20=-103/422, 8-21=-128/425, 9-21=-136/296,
9-10=-156/289

BOT CHORD 1-15=-72/777, 14-15=-72/775, 13-14=-107/535, 12-13=-311/305, 11-12=-481/318
WEBS 3-14=-271/143, 4-14=-11/670, 4-13=-731/50, 5-13=-275/80, 6-13=-3/640, 6-12=-983/41,
7-12=0/880, 7-11=-1251/14, 8-11=-312/168

NOTES- (10)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-9 to 3-1-9, Interior(1) 3-1-9 to 10-0-0, Exterior(2) 10-0-0 to 18-2-15, Interior(1) 18-2-15 to 23-10-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 4) Provide adequate drainage to prevent water ponding.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 10) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard

Job Q104-179RT	Truss T17G	Truss Type GABLE	Qty 1	Ply 1	BANDY RESIDENCE
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8:420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:09:07 2021 Page 1

5-1-12 10-0-0 14-0-0 18-9-4 23-6-8 23-10-0
5-1-12 4-10-4 4-0-0 4-9-4 4-9-4 0-3-8

Scale = 1:65.4




Plate Offsets (X,Y)-- [1:Edge,0-2-12], [3:0-3-4,0-1-12], [4:0-6-4,0-1-12], [7:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.48	Vert(LL) 0.01 in (loc) 9-10 l/defl >999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.65	Vert(CT) 0.01 9-10 >999		
TCDL 10.0	Rep Stress Incr YES	WB 0.41	Horz(CT) -0.02 8 n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 191 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 3-4.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-11, 4-11, 4-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 15-10-0.
(lb) - Max Horz 1=191(LC 13)
Max Uplift All uplift 100 lb or less at joint(s) 1, 11, 9 except 16=363(LC 28), 10=227(LC 5)
Max Grav All reactions 250 lb or less at joint(s) 16, 15, 14, 13, 12, 10 except 1=258(LC 27), 11=1134(LC 1), 9=1304(LC 21)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-34=-261/127, 2-35=-120/579, 3-35=-96/746, 3-36=-8/450, 36-37=-8/450, 4-37=-8/450, 4-38=-91/736, 5-38=-116/482, 5-39=-230/277, 6-39=-369/253, 6-7=-327/212
BOT CHORD 15-16=-357/147, 15-40=-357/147, 14-40=-357/147, 13-14=-357/147, 13-41=-357/147, 12-41=-357/147, 11-12=-357/147, 11-42=-444/268, 10-42=-444/268, 9-10=-444/268
WEBS 2-11=-349/170, 3-11=-778/144, 4-9=-762/153, 5-9=-361/188, 2-16=-229/475, 5-7=-405/594

NOTES- (14)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-1-12 to 3-1-12, Interior(1) 3-1-12 to 10-0-0, Exterior(2) 10-0-0 to 18-2-15, Interior(1) 18-2-15 to 23-8-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Cable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are 2x4 MT20 unless otherwise indicated.
- 7) Gable studs spaced at 2-0-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 10) Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE
Q104-179RT	T17G	GABLE	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:09:07 2021 Page 2

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-_OpL0qMQDhOuAPK2Q66?SuW6Lc1OqNCGceWcfrz467w

NOTES- (14)

- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 11, 9 except (jt=lb) 16=363, 10=227.
- 12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss T18	Truss Type Piggyback Base Girder	Qty 1	Ply 2	BANDY RESIDENCE
-------------------	--------------	-------------------------------------	----------	----------	-----------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine


8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:10:13 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-25oltO9qgziX5YNjHzHT7pFKNcfAH9B_nvV6_0z466u

15-11-0

5-0-3 10-0-0 14-0-0 15-7-8
5-0-3 4-11-13 4-0-0 1-7-80-3-8

Scale = 1:68.8



5-0-3 10-0-0 14-0-0 15-11-0
5-0-3 4-11-13 4-0-0 1-7-80-3-8

Plate Offsets (X,Y)-- [1:Edge,0-2-1], [2:0-0-8,0-1-12], [3:0-6-4,0-1-12], [4:0-2-4,0-1-12], [5:0-2-12,0-1-8], [6:0-2-4,0-1-8], [7:0-5-0,0-5-8], [8:0-4-0,0-5-8], [9:0-5-12,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.76	Vert(LL)	-0.09	8-9	>999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.31	Vert(CT)	-0.15	8-9	>999		
TCDL 10.0	Rep Stress Incr NO	WB 0.68	Horz(CT)	0.01	6	n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S					Weight: 282 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x8 SP 2400F 2.0E
WEBS 2x4 SPF No.2
WEDGE
Left: 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-9-9 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-7, 5-6

REACTIONS. (lb/size) 6=5469/0-6-0 (min. 0-2-4), 1=6073/0-4-0 (min. 0-2-8)
Max Horz 1=266(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-5711/0, 2-3=-3001/0, 3-10=-913/0, 4-10=-913/0, 4-5=-1337/0, 5-6=-4969/0

BOT CHORD 1-11=0/3772, 11-12=0/3772, 12-13=0/3772, 9-13=0/3772, 9-14=0/3772, 14-15=0/3772,
8-15=0/3772, 8-16=0/2071, 16-17=0/2071, 7-17=0/2071

WEBS 2-9=0/3536, 2-8=-2553/0, 3-8=0/4773, 3-7=-3322/0, 4-7=0/726, 5-7=0/4082

NOTES- (13)

1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:

Top chords connected as follows: 2x4 - 1 row at 0-7-0 oc.

Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-6-0 oc.

webs connected as follows: 2x4 - 1 row at 0-9-0 oc.

2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.

3) Unbalanced roof live loads have been considered for this design.

4) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B;
Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip
DOL=1.60

5) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat
roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10, Lu=50-0-0

6) Provide adequate drainage to prevent water ponding.

7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide
will fit between the bottom chord and any other members, with BCDL = 10.0psf.

9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and
referenced standard ANSI/TPI 1.

10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

11) Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 0-6-0 from the left
end to 14-6-0 to connect truss(es) T16 (1 ply 2x4 SPF) to front face of bottom chord.

12) Fill all nail holes where hanger is in contact with lumber.

13) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Continued on page 2

Job Q104-179RT	Truss T18	Truss Type Piggyback Base Girder	Qty 1	Ply 2	BANDY RESIDENCE
-------------------	--------------	-------------------------------------	----------	-----------------	-----------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 10:10:13 2021 Page 2
ID:k67_5nOKmB2GQsoap?Ao4zlytl-25oltO9qgziX5YNjHzHT7pFKNCfAH9B_nvV6_0z466u

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-82, 3-4=-82, 4-5=-82, 1-6=-20

Concentrated Loads (lb)


Vert: 11=-1250(F) 12=-1244(F) 13=-1244(F) 14=-1244(F) 15=-1244(F) 16=-1244(F) 17=-1244(F) 18=-1244(F)

Job Q104-179RT	Truss V01	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:08 2021 Page 1 ID:k67_5nKOKmB2GQsoap?Ao4zlytl-9CT_WbJSir18WmbdUYVW3MZIWUygleRsSR6Hz476

15-5-9
15-5-9

30-11-3
15-5-9

Scale = 1:52.1



30-10-12
30-10-12

30-11-3
0-0-7

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.22	Vert(LL) n/a - n/a 999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.15	Vert(CT) n/a - n/a 999		
TCDL 10.0	Rep Stress Incr YES	WB 0.25	Horz(CT) 0.00 11 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 111 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD
WEBS

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.
1 Row at midpt 6-16

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 30-10-5.

(lb) - Max Horz 1=138(LC 12)

Max Uplift All uplift 100 lb or less at joint(s) 17, 18, 19, 14, 13, 12

Max Grav All reactions 250 lb or less at joint(s) 1, 11 except 16=422(LC 19), 17=525(LC 19), 18=437(LC 19),

19=392(LC 1), 14=525(LC 20), 13=437(LC 20), 12=392(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 6-16=-254/0, 4-17=-347/93, 3-18=-326/80, 2-19=-310/85, 8-14=-347/93, 9-13=-326/80,
10-12=-310/85

NOTES- (10)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=31ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-6-7 to 3-5-9, Interior(1) 3-5-9 to 15-5-9, Exterior(2) 15-5-9 to 18-6-10, Interior(1) 18-6-10 to 30-4-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10

4) All plates are 2x4 MT20 unless otherwise indicated.

5) Gable requires continuous bottom chord bearing.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 17, 18, 19, 14, 13, 12.

9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

10) CUSTOMER SIGNATURE: _____

LOAD CASE(S)


Standard

Job Q104-179RT	Truss V02	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:09 2021 Page 1 ID:k67_5nOKmB2GQsoap?Ao4zlytl-dO1Nkk4T99?8wAp2F0lba6XWwp0PCcrgWC?ekz476

12-0-14
12-0-14

24-1-11
12-0-14

Scale = 1:40.1



24-1-4
24-1-4

24-1-11
0-0-7

Plate Offsets (X,Y)-- [9:0-3-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.21	Vert(LL) n/a	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.16	Vert(CT) n/a		
TCDL 10.0	Rep Stress Incr YES	WB 0.21	Horz(CT) 0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	(loc) - 7		
BCDL 10.0			l/defl n/a		
			L/d 999		

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 24-0-14.

(lb) - Max Horz 1=106(LC 12)

Max Uplift All uplift 100 lb or less at joint(s) 11, 12, 9, 8

Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 10=438(LC 19), 11=451(LC 19), 12=423(LC 1),

9=449(LC 20), 8=424(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 4-10=-255/0, 3-11=-346/93, 2-12=-331/90, 5-9=-345/93, 6-8=-331/90

NOTES- (10)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-6-7 to 3-6-7, Interior(1) 3-6-7 to 12-0-14, Exterior(2) 12-0-14 to 15-0-14, Interior(1) 15-0-14 to 23-7-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10

4) All plates are 2x4 MT20 unless otherwise indicated.

5) Gable requires continuous bottom chord bearing.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11, 12, 9, 8.


9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

10) CUSTOMER SIGNATURE:

LOAD CASE(S)

Standard

Job Q104-179RT	Truss V03	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:10 2021 Page 1 ID:k67_5nOKmB2GQsoap?Ao4zlytl-5bblxHl!EShsl4I?czX_8nehEKAs8ha?uAxYAAz476h



0-0-7 0-0-7	17-4-4 17-3-13				
LOADING (psf) TCLL (roof) 30.0 Snow (Pf/Pg) 30.8/40.0 TCDL 10.0 BCLL 0.0 * BCDL 10.0	SPACING- Plate Grip DOL 1.15 Lumber DOL 1.15 Rep Stress Incr YES Code IRC2015/TPI2014	CSI. TC 0.28 BC 0.12 WB 0.10 Matrix-S	DEFL. Vert(LL) n/a (loc) - l/defl n/a 999 Vert(CT) n/a - n/a 999 Horz(CT) 0.00 5 n/a n/a n/a	PLATES MT20	GRIP 197/144

LUMBER-
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 17-3-6.

(lb) - Max Horz 1=75(LC 12)
Max Uplift All uplift 100 lb or less at joint(s) 9, 6
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 8=305(LC 1), 9=491(LC 1), 6=491(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-9-=387/101, 4-6-=387/101

NOTES- (9)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-6-7 to 3-6-7, Interior(1) 3-6-7 to 8-8-2, Exterior(2) 8-8-2 to 11-8-2, Interior(1) 11-8-2 to 16-9-13 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V04	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional) 8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:10 2021 Page 1 ID:k67_5nOKMb2GQsoap?Ao4zlytl-5bbxHliESHsI4l?czX_8neg?K9n8i7?uAxYAAz476h 5-3-6 5-3-6

10-6-13
5-3-6

Scale = 1:17.1




Plate Offsets (X,Y)-- [2:0-2-12,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.36	Vert(LL) n/a - n/a 999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.19	Vert(CT) n/a - n/a 999		
TCDL 10.0	Rep Stress Incr YES	WB 0.06	Horz(CT) 0.00 3 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 27 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=230/10-5-15 (min. 0-1-8), 3=230/10-5-15 (min. 0-1-8), 4=504/10-5-15 (min. 0-1-8)
Max Horz 1=44(LC 12)
Max Uplift1=7(LC 14), 3=7(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4-355/57

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-6-7 to 3-6-7, Interior(1) 3-6-7 to 5-3-6, Exterior(2) 5-3-6 to 8-3-6, Interior(1) 8-3-6 to 10-0-6 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V05	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	----------------------	----------	----------	-----------------------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine


8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:11 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlyl-Zn878dlK?mPjNEKC9g2Dh?BwrkWpt9K87qh6jcz476g

1-10-11
1-10-11

3-9-5
1-10-11

Scale = 1:8.3



2x4 ≈

2x4 ≈

0-0-7
0-0-7

3-9-5
3-8-14

Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.03	Vert(LL)	n/a	-	n/a	999	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.07	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Rep Stress Incr YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P						Weight: 8 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 3-9-5 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=137/3-8-8 (min. 0-1-8), 3=137/3-8-8 (min. 0-1-8)
Max Horz 1=12(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V06	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	----------------------	----------	----------	-----------------------------


Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:12 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-1z!VMzmy4Xa?OuOjOZSDCk1b7r0bYTlMUQfF2z476f

10-10-10 10-10-10 21-9-4 10-10-10

Scale = 1:62.8



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.23	Vert(LL) in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.14	Vert(CT) -		
TCDL 10.0	Rep Stress Incr YES	WB 0.26	Horz(CT) 7		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	n/a		
BCDL 10.0			n/a		

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD
WEBS

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.
1 Row at midpt 4-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 21-8-12.

(lb) - Max Horz 1=185(LC 12)

Max Uplift All uplift 100 lb or less at joint(s) 1, 7, 12, 13, 10, 8

Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 11=373(LC 19), 12=558(LC 19), 13=386(LC 19),

10=557(LC 20), 8=387(LC 20)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 3-12=-356/166, 2-13=-287/143, 5-10=-356/166, 6-8=-287/143

NOTES- (10)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-4-4 to 3-4-4, Interior(1) 3-4-4 to 10-10-10, Exterior(2) 10-10-10 to 13-10-10, Interior(1) 13-10-10 to 21-5-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10

4) All plates are 2x4 MT20 unless otherwise indicated.

5) Gable requires continuous bottom chord bearing.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7, 12, 13, 10, 8.

9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

10) CUSTOMER SIGNATURE:

LOAD CASE(S) Standard


Job Q104-179RT	Truss V07	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					

8-420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:12 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-1ziVMzmym4Xa?OuOjOZSDCk097rtbaHIMUQfF2z476f

8-10-10
8-10-10

17-9-4
8-10-10

Scale = 1:51.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 2-0-0	TC 0.32	Vert(LL) in (loc) l/defl L/d	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.15	Vert(CT) n/a - n/a 999		
TCDL 10.0	Rep Stress Incr YES	WB 0.15	Horz(CT) 0.00 5 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S			
BCDL 10.0				Weight: 67 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD
WEBS

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.
1 Row at midpt 3-8

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 17-8-12.

(lb) - Max Horz 1=150(LC 12)

Max Uplift All uplift 100 lb or less at joint(s) except 9=-111(LC 14), 6=-111(LC 14)

Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 8=358(LC 19), 9=576(LC 19), 6=576(LC 20)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-9=-407/186, 4-6=-407/186

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-4-4 to 3-4-4, Interior(1) 3-4-4 to 8-10-10, Exterior(2) 8-10-10 to 11-10-10, Interior(1) 11-10-10 to 17-5-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 111 lb uplift at joint 9 and 111 lb uplift at joint 6.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____


LOAD CASE(S) Standard

Job Q104-179RT	Truss V08	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine					Job Reference (optional)

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:13 2021 Page 1
ID:k67_5nKOKmB2GQsoap?Ao4zlytl-VAGtZInaWNfRcYTaH55hmQGChXBCK1YRb8ACnVz476e

6-10-10 13-9-4
6-10-10 6-10-10

Scale = 1:40.2



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.20	in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.14	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.15	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 13-8-12.

(lb) - Max Horz 1=115(LC 12)

Max Uplift All uplift 100 lb or less at joint(s) 1, 8, 6

Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=378(LC 19), 8=419(LC 19), 6=419(LC 20)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-8-=321/159, 4-6-=321/159

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-4-4 to 3-4-4, Interior(1) 3-4-4 to 6-10-10, Exterior(2) 6-10-10 to 9-10-10, Interior(1) 9-10-10 to 13-5-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 8, 6.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V09	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	---

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:14 2021 Page 1

ID:k67_5nKOKmB2GQsoap?Ao4zlytl-_MqGneoDHholEh2nrocwldpLQxXw3VebpovmjxZ476d

4-10-10	9-9-4
4-10-10	4-10-10

$$4 \times 4 =$$

Scale = 1:30.6




Plate Offsets (X,Y)-- [1:0-1-14,0-1-0], [2:0-2-0,0-1-12], [3:0-1-14,0-1-0]

LUMBER-

LUMBER-
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

BRACINGS
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=261/9-8-12 (min. 0-1-8), 3=261/9-8-12 (min. 0-1-8), 4=399/9-8-12 (min. 0-1-8)
Max Horz 1=80(LC 13)
Max Vert 1=16(LC 14), 2=16(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WERS. 3.4 252/22

NOTES- (9)

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-4-4 to 3-4-4, Interior(1) 3-4-4 to 4-10-10, Exterior(2) 4-10-10 to 7-10-10, Interior(1) 7-10-10 to 9-5-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V10	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	----------------------	----------	----------	-----------------------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine


8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:14 2021 Page 1

ID:k67_5nOKmB2GQsoap?Ao4zlytl-_MqGneoDHolEh2nrocwldpOVxZo3WkbpovmJxz476d

2-10-10 5-9-4
2-10-10 2-10-10

4x4 =

Scale = 1:19.2



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.13	in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x4 SPF No.2

OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD

BOT CHORD

Structural wood sheathing directly applied or 5-9-4 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=158/5-8-12 (min. 0-1-8), 3=158/5-8-12 (min. 0-1-8), 4=199/5-8-12 (min. 0-1-8)

Max Horz 1=45(LC 13)

Max Uplift 1=11(LC 14), 3=11(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V12	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	----------------------	----------	----------	-----------------------------

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:16 2021 Page 1

5-0-0

5-0-0

ID:k67_5nOKmB2GQsoap?Ao4zlytl-wly0CKpTpI20T?C9yDeOO2uhdlCFXO2tH6OsOqz476b

10-0-0

5-0-0

Scale = 1:29.2




Plate Offsets (X,Y)-- [1:0-1-14,0-1-0], [2:0-2-0,0-1-12], [3:0-1-14,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.35	Vert(LL) n/a	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Lumber DOL 1.15	BC 0.18	Vert(CT) n/a		
TCDL 10.0	Rep Stress Incr YES	WB 0.10	Horz(CT) 0.00		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-S	(loc) - 3		
BCDL 10.0			l/defl n/a		
			L/d 999		

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=268/9-11-8 (min. 0-1-8), 3=268/9-11-8 (min. 0-1-8), 4=409/9-11-8 (min. 0-1-8)
Max Horz 1=82(LC 12)
Max Uplift 1=11(LC 14), 3=11(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-4=260/33

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) 0-4-4 to 3-4-4, Interior(1) 3-4-4 to 5-0-0, Exterior(2) 5-0-0 to 8-0-0, Interior(1) 8-0-0 to 9-7-12 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job Q104-179RT	Truss V13	Truss Type Valley	Qty 1	Ply 1	BANDY RESIDENCE-BUDGET ONLY
-------------------	--------------	----------------------	----------	----------	-----------------------------


Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Industries, Inc. Mon Jun 21 09:02:17 2021 Page 1

ID:k67_5nOKmB2GQsoap?Ao4zlytl-OxWOPgq5acAs59nMWx9dwGrvX8aQGsS1Vm8QwGz476a
3-0-0 6-0-0
3-0-0 3-0-0

4x4 =

Scale = 1:19.8



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.15	in (loc)	MT20	197/144
Snow (Pf/Pg) 30.8/40.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x4 SPF No.2

OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD

BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=165/5-11-8 (min. 0-1-8), 3=165/5-11-8 (min. 0-1-8), 4=208/5-11-8 (min. 0-1-8)

Max Horz 1=47(LC 12)

Max Uplift 1=12(LC 14), 3=12(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	BANDY RESIDENCE-BUDGET ONLY
Q104-179RT	V14	Valley	1	1	Job Reference (optional)

Fairman's Roof Trusses, Inc., Creekside, PA 15732, Mike Repine

8.420 s Dec 30 2020 MiTek Inc.

8.420 3 Dec 30 2020 MIFtek Industries, Inc. Mon Jun 21 09:32:11 2021 Page 1
b?Ao4zlytl-OxWOPgg5acAs59nMWx9dwGRxk8a7Gsp1Vm8QwGz476a

ID:k67_5nKOKmB2GQssoap?Ao4zlytl-OxWOPqg5acAss59nMWx9dwGRxk8a7Gsp1Vm8QwGz476a

1-0-0	—	2-0-0
1-0-0	—	1-0-0

Scale = 1:7.8




Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2

BRACING-

BRACES
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=66/1-11-8 (min. 0-1-8), 3=66/1-11-8 (min. 0-1-8)
Max Horz 1=11(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=40.0 psf (ground snow); Pf=30.8 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10

4) Gable requires continuous bottom chord bearing.

5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

8) CUSTOMER SIGNATURE: _____

LOAD CASE(S) Standard